Extracted by GlobalMSDS Ltd

12 March 2019

1910.1043(a)

Scope and application.

1910.1043(a)(1)

This section, in its entirety, applies to the control of employee exposure to cotton dust in all workplaces where employees engage in yarn manufacturing, engage in slashing and weaving operations, or work in waste houses for textile operations.

1910.1043(a)(2)

This section does not apply to the handling or processing of woven or knitted materials; to maritime operations covered by 29 CFR Parts 1915 and 1918; to harvesting or ginning of cotton; or to the construction industry.

1910.1043(a)(3)

Only paragraphs (h) Medical surveillance, (k)(2) through (4) Recordkeeping - Medical Records, and Appendices B, C and D of this section apply in all work places where employees exposed to cotton dust engage in cottonseed processing or waste processing operations. 1910.1043(a)(4)

This section applies to yarn manufacturing and slashing and weaving operations exclusively using washed cotton (as defined by paragraph (n) of this section) only to the extent specified by paragraph (n) of this section.

1910.1043(a)(5)

This section, in its entirety, applies to the control of all employees exposure to the cotton dust generated in the preparation of washed cotton from opening until the cotton is thoroughly wetted. 1910.1043(a)(6)

This section does not apply to knitting, classing or warehousing operations except that employers with these operations, if requested by NIOSH, shall grant NIOSH access to their employees and workplaces for exposure monitoring and medical examinations for purposes of a health study to be performed by NIOSH on a sampling basis.

1910.1043(b)

Definitions. For the purpose of this section:

Assistant Secretary means the Assistant Secretary of Labor for Occupational Safety and Health, U.S. Department of Labor, or designee;

Blow down means the general cleaning of a room or a part of a room by the use of compressed air.

Blow off means the use of compressed air for cleaning of short duration and usually for a specific machine or any portion of a machine.

Cotton dust means dust present in the air during the handling or processing of cotton, which may contain a mixture of many substances including ground up plant matter, fiber, bacteria, fungi, soil, pesticides,non-cotton plant matter and other contaminants which may have accumulated with the cotton during the growing, harvesting and subsequent processing or storage periods. Any dust present during the handling and processing of cotton through the weaving or knitting of fabrics, and dust present in other operations or manufacturing processes using raw or waste cotton fibers or cotton fiber byproducts from textile mills are considered cotton dust within this definition. Lubricating oil mist associated with weaving operations is not considered cotton dust.

Director means the Director of the National Institute for Occupational Safety and Health (NIOSH), U.S. Department of Health and Human Services, or designee.

Equivalent Instrument means a cotton dust sampling device that meets the vertical elutriator equivalency requirements as described in paragraph (d)(1)(iii) of this section.

Lint-free respirable cotton dust means particles of cotton dust of approximately 15 micrometers or less aerodynamic equivalent diameter;

Vertical elutriator cotton dust sampler or vertical elutriator means a dust sampler which has a particle size cut-off at approximately 15 micrometers aerodynamic equivalent diameter when operating at the flow rate of 7.4 + or - 0.2 liters of air per minute;

Waste processing means waste recycling (sorting, blending, cleaning and willowing) and garnetting.

Extracted by GlobalMSDS Ltd

12 March 2019

Yarn manufacturing means all textile mill operations from opening to, but not including, slashing and weaving.

1910.1043(c)

Permissible exposure limits and action levels -

1910.1043(c)(1)

Permissible exposure limits (PEL).

1910.1043(c)(1)(i)

The employer shall assure that no employee who is exposed to cotton dust in yarn manufacturing and cotton washing operations is exposed to airborne concentrations of lint-free respirable cotton dust greater than 200 ug/m³ mean concentration, averaged over an eight-hour period, as measured be a vertical elutriator or an equivalent instrument.

1910.1043(c)(1)(ii)

The employer shall assure that no employee who is exposed to cotton dust in textile mill waste house operations or is exposed in yarn manufacturing to dust from "lower grade washed cotton" as defined in paragraph (n)(5) of this section is exposed to airborne concentrations of lint-free respirable cotton dust greater than 500 ug/m³ mean concentration, averaged over an eight-hour period, as measured by a vertical elutriator or an equivalent instrument.

1910.1043(c)(1)(iii)

The employer shall assure that no employee who is exposed to cotton dust in the textile processes known as slashing and weaving is exposed to airborne concentrations of lint-free respirable cotton dust greater than 750 ug/m³ mean concentration, averaged over an eight hour period, as measured by a vertical elutriator or an equivalent instrument.

1910.1043(c)(2)

Action levels.

1910.1043(c)(2)(i)

The action level for yarn manufacturing and cotton washing operations is an airborne concentration of lint-free respirable cotton dust of 100 ug/m³ mean concentration, averaged over an eight-hour period, as measured by a vertical elutriator or an equivalent instrument. 1910.1043(c)(2)(ii)

The action level for waste houses for textile operations is an airborne concentration of lint-free respirable cotton dust of 250 ug/m³ mean concentration, averaged over an eight-hour period, as measured by a vertical elutriator or an equivalent instrument.

1910.1043(c)(2)(iii)

The action level for the textile processes known as slashing and weaving is an airborne concentration of lint-free respirable cotton dust of 375 ug/m³ mean concentration, averaged over an eight-hour period, as measured by a vertical elutriator or an equivalent instrument. 1910.1043(d)

Exposure monitoring and measurement -

1910.1043(d)(1)

General.

1910.1043(d)(1)(i)

For the purposes of this section, employee exposure is that exposure which would occur if the employee were not using a respirator.

1910.1043(d)(1)(ii)

The sampling device to be used shall be either the vertical elutriator cotton dust sampler or an equivalent instrument.

1910.1043(d)(1)(iii)

If an alternative to the vertical elutriator cotton dust sampler is used, the employer shall establish equivalency by reference to an OSHA opinion or by documenting, based on data developed by the employer or supplied by the manufacturer, that the alternative sampling devices meets the following criteria:

1910.1043(d)(1)(iii)(A)

It collects respirable particulates in the same range as the vertical elutriator (approximately 15 microns);

1910.1043(d)(1)(iii)(B)

Replicate exposure data used to establish equivalency are collected in side-by-side field and laboratory comparisons; and

1910.1043(d)(1)(iii)(C)

A minimum of 100 samples over the range of 0.5 to 2 times the permissible exposure limit are collected, and 90% of these samples have an accuracy range of plus or minus 25 per cent of the vertical elutriator reading with a 95% confidence level as demonstrated by a statistically valid

Extracted by GlobalMSDS Ltd

12 March 2019

protocol. (An acceptable protocol for demonstrating equivalency is described in Appendix E of this section.)

1910.1043(d)(1)(iv)

OSHA will issue a written opinion stating that an instrument is equivalent to a vertical elutriator cotton dust sampler if

1910.1043(d)(1)(iv)(A)

A manufacturer or employer requests an opinion in writing and supplies the following information: 1910.1043(d)(1)(iv)(A)(1)

Sufficient test data to demonstrate that the instrument meets the requirements specified in this paragraph and the protocol specified in Appendix E of this section;

1910.1043(d)(1)(iv)(A)(2)

Any other relevant information about the instrument and its testing requested by OSHA; and 1910.1043(d)(1)(iv)(A)(3)

A certification by the manufacturer or employer that the information supplied is accurate, and 1910.1043(d)(1)(iv)(B)

if OSHA finds, based on information submitted about the instrument, that the instrument meets the requirements for equivalency specified by paragraph (d) of this section.

1910.1043(d)(2)

Initial monitoring. Each employer who has a place of employment within the scope of paragraph (a)(1), (a)(4), or (a)(5) of this section shall conduct monitoring by obtaining measurements which are representative of the exposure of all employees to airborne concentrations of lint-free respirable cotton dust over an eight-hour period. The sampling program shall include at least one determination during each shift for each work area.

1910.1043(d)(3)

Periodic monitoring.

1910.1043(d)(3)(i)

If the initial monitoring required by paragraph (d)(2) of this section or any subsequent monitoring reveals employee exposure to be at or below the permissible exposure limit, the employer shall repeat the monitoring for those employees at least annually.

1910.1043(d)(3)(ii)

If the initial monitoring required by paragraph (d)(2) of this section or any subsequent monitoring reveals employee exposure to be above the PEL, the employer shall repeat the monitoring for those employees at least every six months.

1910.1043(d)(3)(iii)

Whenever there has been a production, process, or control change which may result in new or additional exposure to cotton dust, or whenever the employer has any other reason to suspect an increase in employee exposure, the employer shall repeat the monitoring and measurements for those employees affected by the change or increase.

1910.1043(d)(4)

Employee notification.

1910.1043(d)(4)(i)

The employer must, within 15 working days after the receipt of the results of any monitoring performed under this section, notify each affected employee of these results either individually in writing or by posting the results in an appropriate location that is accessible to employees. 1910.1043(d)(4)(ii)

Whenever the results indicate that the employee's exposure exceeds the applicable permissible exposure limit specified in paragraph (c) of this section, the employer shall include in the written notice a statement that the permissible exposure limit was exceeded and a description of the corrective action taken to reduce exposure below the permissible exposure limit.

1910.1043(e)

Methods of compliance -

1910.1043(e)(1)

Engineering and work practice controls. The employer shall institute engineering and work practice controls to reduce and maintain employee exposure to cotton dust at or below the permissible exposure limit specified in paragraph (c) of this section, except to the extent that the employer can establish that such controls are not feasible.

1910.1043(e)(2)

Whenever feasible engineering and work practice controls are not sufficient to reduce employee exposure to or below the permissible exposure limit, the employer shall nonetheless institute these controls to reduce exposure to the lowest feasible level, and shall supplement these controls with the use of respirators which shall comply with the provisions of paragraph (f) of this section. 1910.1043(e)(3)

Compliance program.

Extracted by GlobalMSDS Ltd

12 March 2019

1910.1043(e)(3)(i)

Where the most recent exposure monitoring data indicates that any employee is exposed to cotton dust levels greater than the permissible exposure limit, the employer shall establish and implement a written program sufficient to reduce exposures to or below the permissible exposure limit solely by means of engineering controls and work practices as required by paragraph (e)(1) of this section.

1910.1043(e)(3)(ii)

The written program shall include at least the following:

1910.1043(e)(3)(ii)(A)

A description of each operation or process resulting in employee exposure to cotton dust at levels greater than the PEL;

1910.1043(e)(3)(ii)(B)

Engineering plans and other studies used to determine the controls for each process;

1910.1043(e)(3)(ii)(C)

A report of the technology considered in meeting the permissible exposure limit;

1910.1043(e)(3)(ii)(D)

Monitoring data obtained in accordance with paragraph (d) of this section;

1910.1043(e)(3)(ii)(E)

A detailed schedule for development and implementation of engineering and work practice controls, including exposure levels projected to be achieved by such controls;

1910.1043(e)(3)(ii)(F)

Work practice program; and

1910.1043(e)(3)(ii)(G)

Other relevant information.

1910.1043(e)(3)(iii)

The employer's schedule as set forth in the compliance program, shall project completion of the implementation of the compliance program no later than March 27, 1984 or as soon as possible if monitoring after March 27, 1984 reveals exposures over the PEL, except as provided in paragraph (m)(2)(ii)(B) of this section.

1910.1043(e)(3)(iv)

The employer shall complete the steps set forth in his program by the dates in the schedule. 1910.1043(e)(3)(v)

Written programs shall be submitted, upon request, to the Assistant Secretary and the Director, and shall be available at the worksite for examination and copying by the Assistant Secretary, the Director, and any affected employee or their designated representatives.

1910.1043(e)(3)(vi)

The written program required under paragraph (e)(3) of this section shall be revised and updated when necessary to reflect the current status of the program and current exposure levels.

1910.1043(e)(4)

Mechanical ventilation. When mechanical ventilation is used to control exposure, measurements which demonstrate the effectiveness of the system to control exposure, such as capture velocity, duct velocity, or static pressure shall be made at reasonable intervals.

1910.1043(f)

Respiratory protection.

1910.1043(f)(1)

General. For employees who are required to use respirators by this section, the employer must provide each employee an appropriate respirator that complies with the requirements of this paragraph. Respirators must be used during:

1910.1043(f)(1)(i)

Periods necessary to install or implement feasible engineering and work-practice controls. 1910.1043(f)(1)(ii)

Maintenance and repair activities for which engineering and work-practice controls are not feasible.

1910.1043(f)(1)(iii)

Work operations for which feasible engineering and work-practice controls are not yet sufficient to reduce employee exposure to or below the permissible exposure limits.

1910.1043(f)(1)(iv)

Work operations specified under paragraph (g)(1) of this section.

1910.1043(f)(1)(v)

Periods for which an employee requests a respirator.

1910.1043(f)(2)

Respirator program.

1910.1043(f)(2)(i)

Extracted by GlobalMSDS Ltd

12 March 2019

The employer must implement a respiratory protection program in accordance with § 1910.134(b) through (d) (except (d)(1)(iii)), and (f) through (m), which covers each employee required by this section to use a respirator.

1910.1043(f)(2)(ii)

Whenever a physician determines that an employee who works in an area in which the cotton-dust concentration exceeds the PEL is unable to use a respirator, including a powered air-purifying respirator, the employee must be given the opportunity to transfer to an available position, or to a position that becomes available later, that has a cotton-dust concentration at or below the PEL. The employer must ensure that such employees retain their current wage rate or other benefits as a result of the transfer.

1910.1043(f)(3)

Respirator selection.

1910.1043(f)(3)(i)

Employers must:

1910.1043(f)(3)(i)(A)

Select, and provide to employees, the appropriate respirators specified in paragraph (d)(3)(i)(A) of 29 CFR 1910.134; however, employers must not select or use filtering facepieces for protection against cotton dust concentrations greater than five times (5 x) the PEL.:

1910.1043(f)(3)(i)(B)

Provide HEPA filters for powered and non-powered air-purifying respirators used at cotton dust concentrations greater than ten times (10 x) the PEL.

1910.1043(f)(3)(ii)

Employers must provide an employee with a powered air-purifying respirator (PAPR) instead of a non-powered air-purifying respirator selected according to paragraph (f)(3)(i) of this standard when the employee chooses to use a PAPR and it provides adequate protection to the employee as specified by paragraph (f)(3)(i) of this standard.

1910.1043(g)

Work practices. Each employer shall, regardless of the level of employee exposure, immediately establish and implement a written program of work practices which shall minimize cotton dust exposure. The following shall be included were applicable:

1910.1043(g)(1)

Compressed air "blow down" cleaning shall be prohibited where alternative means are feasible. Where compressed air is used for cleaning, the employees performing the "blow down" or "blow off" shall wear suitable respirators. Employees whose presence is not required to perform "blow down" or "blow off" shall be required to leave the area affected by the "blow down" or "blow off" during this cleaning operation.

1910.1043(g)(2)

Cleaning of clothing or floors with compressed air shall be prohibited.

1910.1043(g)(3)

Floor sweeping shall be performed with a vacuum or with methods designed to minimize dispersal of dust.

1910.1043(g)(4)

In areas where employees are exposed to concentrations of cotton dust greater than the permissible exposure limit, cotton and cotton waste shall be stacked, sorted, baled, dumped, removed or otherwise handled by mechanical means, except where the employer can show that it is infeasible to do so. Where infeasible, the method used for handling cotton and cotton waste shall be the method which reduces exposure to the lowest level feasible.

1910.1043(h)

Medical surveillance -

1910.1043(h)(1)

General.

1910.1043(h)(1)(i)

Each employer covered by the standard shall institute a program of medical surveillance for all employees exposed to cotton dust.

1910.1043(h)(1)(ii)

The employer shall assure that all medical examinations and procedures are performed by or under the supervision of a licensed physician and are provided without cost to the employee. 1910.1043(h)(1)(iii)

Persons other than licensed physicians, who administer the pulmonary function testing required by this section shall have completed a NIOSH-approved training course in spirometry.

1910.1043(h)(2)

Extracted by GlobalMSDS Ltd

12 March 2019

Initial examinations. The employer shall provide medical surveillance to each employee who is or may be exposed to cotton dust. For new employees, this examination shall be provided prior to initial assignment. The medical surveillance shall include at least the following:

1910.1043(h)(2)(i)

A medical history;

1910.1043(h)(2)(ii)

The standardized questionnaire contained in Appendix B; and

1910.1043(h)(2)(iii)

A pulmonary function measurement, including a determination of forced vital capacity (FVC) and forced expiratory volume in one second (FEV(1)), the FEV(1)/FVC ratio, and the percentage that the measured values of FEV(1) and FVC differ from the predicted values, using the standard tables in Appendix C. These determinations shall be made for each employee before the employee enters the workplace on the first day of the work week, preceded by at least 35 hours of no exposure to cotton dust. The tests shall be repeated during the shift, no less than 4 and no more than 10 hours after the beginning of the work shift; and, in any event, no more than one hour after cessation of exposure. Such exposure shall be typical of the employee's usual workplace exposure. The predicted FEV(1) and FVC for blacks shall be multiplied by 0.85 to adjust for ethnic differences.

1910.1043(h)(2)(iv)

Based upon the questionnaire results, each employee shall be graded according to Schilling's byssinosis classification system.

1910.1043(h)(3)

Periodic examinations.

1910.1043(h)(3)(i)

The employer shall provide at least annual medical surveillance for all employees exposed to cotton dust above the action level in yarn manufacturing, slashing and weaving, cotton washing and waste house operations. The employer shall provide medical surveillance at least every two years for all employees exposed to cotton dust at or below the action level, for all employees exposed to cotton dust from washed cotton (except from washed cotton defined in paragraph (n)(3) of this section), and for all employees exposed to cotton dust in cottonseed processing and waste processing operations. Periodic medical surveillance shall include at least an update of the medical history, standardized questionnaire (App. B-111), Schilling byssinosis grade, and the pulmonary function measurements in paragraph (h)(2)(iii) of this section.

. 1910.1043(h)(3)(ii)

Medical surveillance as required in paragraph (h)(3)(i) of this section shall be provided every six months for all employees in the following categories:

1910.1043(h)(3)(ii)(A)

An FEV(1) of greater than 80 percent of the predicted value, but with an FEV(1) decrement of 5 percent or 200 ml. on a first working day;

1910.1043(h)(3)(ii)(B)

An FEV(1) of less than 80 percent of the predicted value; or

1910.1043(h)(3)(ii)(C)

Where, in the opinion of the physician, any significant change in questionnaire findings, pulmonary function results, or other diagnostic tests have occurred.

1910.1043(h)(3)(iii)

An employee whose FEV(1) is less than 60 percent of the predicted value shall be referred to a physician for a detailed pulmonary examination.

1910.1043(h)(3)(iv)

A comparison shall be made between the current examination results and those of previous examinations and a determination made by the physician as to whether there has been a significant change.

1910.1043(h)(4)

Information provided to the physician. The employer shall provide the following information to the examination physician:

1910.1043(h)(4)(i)

A copy of this regulation and its Appendices:

1910.1043(h)(4)(ii)

A description of the affected employee's duties as they relate to the employee's exposure; 1910.1043(h)(4)(iii)

The employee's exposure level or anticipated exposure level;

1910.1043(h)(4)(iv)

A description of any personal protective equipment used or to be used; and 1910.1043(h)(4)(v)

Extracted by GlobalMSDS Ltd

12 March 2019

Information from previous medical examinations of the affected employee which is not readily available to the examining physician.

1910.1043(h)(5)

Physician's written opinion.

1910.1043(h)(5)(i)

The employer shall obtain and furnish the employee with a copy of a written opinion from the examining physician containing the following:

1910.1043(h)(5)(i)(A)

The results of the medical examination and tests including the FEV(1), FVC, AND FEV(1)/FVC ratio:

1910.1043(h)(5)(i)(B)

The physician's opinion as to whether the employee has any detected medical conditions which would place the employee at increased risk of material impairment of the employee's health from exposure to cotton dust;

1910.1043(h)(5)(i)(C)

The physician's recommended limitations upon the employee's exposure to cotton dust or upon the employee's use of respirators including a determination of whether an employee can wear a negative pressure respirator, and where the employee cannot, a determination of the employee's ability to wear a powered air purifying respirator; and,

1910.1043(h)(5)(i)(D)

A statement that the employee has been informed by the physician of the results of the medical examination and any medical conditions which require further examination or treatment. 1910.1043(h)(5)(ii)

The written opinion obtained by the employer shall not reveal specific findings or diagnoses unrelated to occupational exposure.

1910.1043(i)

Employee education and training -

1910.1043(i)(1)

Training program.

1910.1043(i)(1)(i)

The employer shall train each employee exposed to cotton dust in accordance with the requirements of this section. The employer shall institute a training program and ensure employee participation in the program.

1910.1043(i)(1)(ii)

The training program shall be provided prior to initial assignment and shall be repeated annually for each employee exposed to cotton dust, when job assignments or work processes change and when employee performance indicates a need for retraining.

1910.1043(i)(2)

Access to training materials.

1910.1043(i)(2)(i)

Each employer shall post a copy of this section with its appendices in a public location at the workplace, and shall, upon request, make copies available to employees.

1910.1043(i)(2)(ii)

The employer shall provide all materials relating to the employee training and information program to the Assistant Secretary and the Director upon request.

1910.1043(j)

Signs.

1910.1043(j)(1)

The employer shall post the following warning sign in each work area where the permissible exposure limit for cotton dust is exceeded:

DANGER

COTTON DUST

CAUSES DAMAGE TO LUNGS

(BYSSINOSIS)

WEAR RESPIRATORY PROTECTION IN THIS AREA

1910.1043(j)(2)

Prior to June 1, 2016, employers may use the following legend in lieu of that specified in paragraph (j)(1) of this section:

WARNING

COTTON DUST WORK AREA

MAY CAUSE ACUTE OR DELAYED

Extracted by GlobalMSDS Ltd

12 March 2019

LUNG INJURY

(BYSSINOSIS)

RESPIRATORS

REQUIRED IN THIS AREA

1910.1043(k)

Recordkeeping -

1910.1043(k)(1)

Exposure measurements.

1910.1043(k)(1)(i)

The employer shall establish and maintain an accurate record of all measurements required by paragraph (d) of this section.

1910.1043(k)(1)(ii)

The record shall include:

1910.1043(k)(1)(ii)(A)

A log containing the items listed in paragraph IV (a) of Appendix A, and the dates, number, duration, and results of each of the samples taken, including a description of the procedure used to determine representative employee exposure;

1910.1043(k)(1)(ii)(B)

The type of protective devices worn, if any, and length of time worn; and

1910.1043(k)(1)(ii)(C)

The names, social security numbers, job classifications, and exposure levels of employees whose exposure the measurement is intended to represent.

1910.1043(k)(1)(iii)

The employer shall maintain this record for at least 20 years.

1910.1043(k)(2)

Medical surveillance.

1910.1043(k)(2)(i)

The employer shall establish and maintain an accurate medical record for each employee subject to medical surveillance required by paragraph (h) of this section.

1910.1043(k)(2)(ii)

The record shall include:

1910.1043(k)(2)(ii)(A)

The name and social security number and description of the duties of the employee;

1910.1043(k)(2)(ii)(B)

A copy of the medical examination results including the medical history, questionnaire response, results of all tests, and the physician's recommendation;

1910.1043(k)(2)(ii)(C)

A copy of the physician's written opinion;

1910.1043(k)(2)(ii)(D)

Any employee medical complaints related to exposure to cotton dust;

1910.1043(k)(2)(ii)(E)

A copy of this standard and its appendices, except that the employer may keep one copy of the standard and the appendices for all employees, provided that he references the standard and appendices in the medical surveillance record of each employee; and

1910.1043(k)(2)(ii)(F)

A copy of the information provided to the physician as required by paragraph (h)(4) of this section. 1910.1043(k)(2)(iii)

The employer shall maintain this record for at least 20 years.

1910.1043(k)(3)

Availability.

1910.1043(k)(3)(i)

The employer shall make all records required to be maintained by paragraph (k) of this section available to the Assistant Secretary and the Director for examination and copying.

1910.1043(k)(3)(ii)

Employee exposure measurement records and employee medical records required by this paragraph shall be provided upon request to employees, designated representatives, and the Assistant Secretary in accordance with 29 CFR 1910.1020(a) through (e) and (g) through (i). 1910.1043(k)(4)

Transfer of records.

1910.1043(k)(4)(i)

Whenever the employer ceases to do business, the successor employer shall receive and retain all records required to be maintained by paragraph (k) of this section.

1910.1043(k)(4)(ii)

Extracted by GlobalMSDS Ltd

12 March 2019

The employer shall also comply with any additional requirements involving transfer of records set forth in 29 CFR 1910.1020(h).

1910.1043(I)

Observation of monitoring.

1910.1043(I)(1)

The employer shall provide affected employees or their designated representatives an opportunity to observe any measuring or monitoring of employee exposure to cotton dust conducted pursuant to paragraph (d) of this section.

1910.1043(I)(2)

Whenever observation of the measuring or monitoring of employee exposure to cotton dust requires entry into an area where the use of personal protective equipment is required, the employer shall provide the observer with and assure the use of such equipment and shall require the observer to comply with all other applicable safety and health procedures. 1910.1043(I)(3)

Without interfering with the measurement, observers shall be entitled to:

1910.1043(I)(3)(i)

An explanation of the measurement procedures:

1910.1043(I)(3)(ii)

An opportunity to observe all steps related to the measurement of airborne concentrations of cotton dust performed at the place of exposure; and

1910.1043(I)(3)(iii)

An opportunity to record the results obtained.

1910.1043(m)

Washed Cotton-

1910.1043(m)(1)

Exemptions. Cotton, after it has been washed by the processes described in this paragraph, is exempt from all or parts of this section as specified if the requirements of this paragraph are met.

1910.1043(m)(2)

Initial requirements.

1910.1043(m)(2)(i)

In order for an employer to qualify as exempt or partially exempt from this standard for operations using washed cotton, the employer must demonstrate that the cotton was washed in a facility which is open to inspection by the Assistant Secretary and the employer must provide sufficient accurate documentary evidence to demonstrate that the washing methods utilized meet the requirements of this paragraph.

1910.1043(m)(2)(ii)

An employer who handles or processes cotton which has been washed in a facility not under the employer's control and claims an exemption or partial exemption under this paragraph, must obtain from the cotton washer and make available at the worksite, to the Assistant Secretary, to any affected employee, or to their designated representative the following:

1910.1043(m)(2)(ii)(A)

A certification by the washer of the cotton of the grade of cotton, the type of washing process, and that the batch meets the requirements of this paragraph:

1910.1043(m)(2)(ii)(B)

Sufficient accurate documentation by the washer of the cotton grades and washing process; and

1910.1043(m)(2)(ii)(C)

An authorization by the washer that the Assistant Secretary or the Director may inspect the washer's washing facilities and documentation of the process.

1910.1043(m)(3)

Medical and dyed cotton. Medical grade (USP) cotton, cotton that has been scoured, bleached and dyed, and mercerized yarn shall be exempt from all provisions of this standard.

1910.1043(m)(4)

Higher grade washed cotton. The handling or processing of cotton classed as "low middling light spotted or better" (color grade 52 or better and leaf grade code 5 or better according to the 1993 USDA classification system) shall be exempt from all provisions of the standard except the requirements of paragraphs (h) medical surveillance, (k)(2) through (4) recordkeeping—medical

Extracted by GlobalMSDS Ltd

12 March 2019

records, and Appendices B, C, and D of this section, if they have been washed on one of the following systems:

1910.1043(m)(4)(i)

On a continuous batt system or a rayon rinse system including the following conditions:

1910.1043(m)(4)(i)(A)

With water;

1910.1043(m)(4)(i)(B)

At a temperature of no less than 60 °C;

1910.1043(m)(4)(i)(C)

With a water-to-fiber ratio of no less than 40:1; and

1910.1043(m)(4)(i)(D)

With the bacterial levels in the wash water controlled to limit bacterial contamination of the cotton.

1910.1043(m)(4)(ii)

On a batch kier washing system including the following conditions:

1910.1043(m)(4)(ii)(A)

With water;

1910.1043(m)(4)(ii)(B)

With cotton fiber mechanically opened and thoroughly prewetted before forming the cake;

1910.1043(m)(4)(ii)(C)

For low-temperature processing, at a temperature of no less than 60 °C with a water-to-fiber ratio of no less than 40:1; or, for high-temperature processing, at a temperature of no less than 93 °C with a water-to-fiber ratio of no less than 15:1;

1910.1043(m)(4)(ii)(D)

With a minimum of one wash cycle followed by two rinse cycles for each batch, using fresh water in each cycle, and

1910.1043(m)(4)(ii)(E)

With bacterial levels in the wash water controlled to limit bacterial contamination of the cotton.

1910.1043(m)(5)

Lower grade washed cotton. The handling and processing of cotton of grades lower than "low middling light spotted," that has been washed as specified in paragraph (n)(4) of this section and has also been bleached, shall be exempt from all provisions of the standard except the requirements of paragraphs (c)(1)(ii) Permissible Exposure Limit, (d) Exposure Monitoring, (h) Medical Surveillance, (k) Recordkeeping, and Appendices B, C and D of this section.

1910.1043(m)(6)

Mixed grades of washed cotton. If more than one grade of washed cotton is being handled or processed together, the requirements of the grade with the most stringent exposure limit, medical and monitoring requirements shall be followed.

1910.1043(n)

Appendices.

1910.1043(n)(1)

Appendices B, C, and D of this section are incorporated as part of this section and the contents of these appendices are mandatory.

1910.1043(n)(2)

Appendix A of this section contains information which is not intended to create any additional obligations not otherwise imposed or to detract from any existing obligations.

1910.1043(n)(3)

Medical and dyed cotton. Medical grade (USP) cotton, cotton that has been scoured, bleached and dyed, and mercerized yarn shall be exempt from all provisions of this standard.

[61 FR 5507, Feb. 13, 1996; 63 FR 1152, Jan. 8, 1998; 65 FR 76567, Dec. 7, 2000; 70 FR 1142, Jan. 5, 2005; 71 FR 16672, April 3, 2006; 71 FR 50189, August 24, 2006; 73 FR 75586, Dec. 12, 2008; 76 FR 33609, June 8, 2011; 77 FR 17782, March 26, 2012; 83 FR 30035, June 27, 2018]

Extracted by GlobalMSDS Ltd 12 March 2019

I. SAMPLING LOCATIONS

The sampling procedures must be designed so that samples of the actual dust concentrations are collected accurately and consistently and reflect the concentrations of dust at the place and time of sampling. Sufficient number of 6-hour area samples in each distinct work area of the plant should be collected at locations which provide representative samples of air to which the worker is exposed. In order to avoid filter overloading, sampling time may be shortened when sampling in dusty areas. Samples in each work area should be gathered simultaneously or sequentially during a normal operating period. The daily time-weighted average (TWA) exposure of each worker can then be determined by using the following formula:

Summation of hours spent in each location and the dust concentration in that location.

Total hours exposed

A time-weighted average concentration should be computed for each

worker and properly logged and maintained on file for review.

II. SAMPLING EQUIPMENT

- (a) Sampler. The instrument selected for monitoring is the Lumsden-Lynch vertical elutriator. It should operate at a flow rate of 7.4 + or 0.2 liters/minute. The samplers should be cleaned prior to sampling. The pumps should be monitored during sampling.
- (b) Filter Holder. A three-piece cassette constructed of polystyrene designed to hold a 37-mm diameter filter should be used. Care must be exercised to insure that an adequate seal exists between elements of the cassette.
- (c) Filters and Support Pads. The membrane filters used should be polyvinyl chloride with a 5-um pore size and 37-mm diameter. A support pad, commonly called a backup pad, should be used under the filter membrane in the field monitor cassette.
- (d) Balance. A balance sensitive to 10 micrograms should be used.
- (e) Monitoring equipment for use in Class III hazardous locations must be approved for use in such locations, in accordance with the requirements of the OSHA electrical standards in Subpart S of Part 1910.

III. INSTRUMENT CALIBRATION PROCEDURE

Samplers shall be calibrated when first received from the factory, after repair, and after receiving any abuse. The samplers should be calibrated in the laboratory both before they are used in the field and after they have been used to collect a large number of field samples. The primary standard, such as a spirometer or other standard calibrating instruments such as a wet test meter or a large bubble meter or dry gas meter, should be used. Instructions for calibration with the wet test meter follow. If another calibration device is selected, equivalent procedures should be used:

- (a) Level wet test meter. Check the water level which should just touch the calibration point at the left side of the meter. If water level is low, add water 1-2 deg. F. warmer than room temperature of till point. Run the meter for 30 minutes before calibration;
- (b) Place the polyvinyl chloride membrane filter in the filter cassette;
- (c) Assemble the calibration sampling train;
- (d) Connect the wet test meter to the train.

The pointer on the meter should run clockwise and a pressure drop of not more than 1.0 inch of water indicated. If the pressure drop is greater than 1.0, disconnect and check the system;

(e) Operate the system for ten minutes before starting the calibration;

Extracted by GlobalMSDS Ltd

- 12 March 2019
- (f) Check the vacuum gauge on the pump to insure that the pressure drop across the orifice exceeds 17 inches of mercury;
- (g) Record the following on calibration data sheets:
- (1) Wet test meter reading, start and finish;
- (2) Elapsed time, start and finish (at least two minutes);
- (3) Pressure drop at manometer;
- (4) Air temperature;
- (5) Barometric pressure; and
- (6) Limiting orifice number;
- (h) Calculate the flow rate and compare against the flow of 7.4 + or 0.2 liters/minute. If flow is between these limits, perform calibration again, average results, and record orifice number and flow rate. If flow is not within these limits, discard or modify orifice and repeat procedure;
- (i) Record the name of the person performing the calibration, the date, serial number of the wet test meter, and the number of the critical orifices being calibrated.

IV. SAMPLING PROCEDURE

- (a) Sampling data sheets should include a log of:
- (1) The date of the sample collection;
- (2) The time of sampling;
- (3) The location of the sampler;
- (4) The sampler serial number;
- (5) The cassette number;
- (6) The time of starting and stopping the sampling and the duration of sampling;
- (7) The weight of the filter before and after sampling;
- (8) The weight of dust collected (corrected for controls);
- (9) The dust concentration measured;
- (10) Other pertinent information; and
- (11) Name of person taking sample
- (b) Assembly of filter cassette should be as follows:
- (1) Loosely assemble 3-piece cassette;
- (2) Number cassette;
- (3) Place absorbent pad in cassette;
- (4) Weigh filter to an accuracy of 10 ug;
- (5) Place filter in cassette;
- (6) Record weight of filter in log, using cassette number for identification;
- (7) Fully assemble cassette, using pressure to force parts tightly together;
- (8) Install plugs top and bottom;
- (9) Put shrink band on cassette, covering joint between center and bottom parts of cassette; and
- (10) Set cassette aside until shrink band dries thoroughly.
- (c) Sampling collection should be performed as follows:
- (1) Clean lint out of the motor and elutriator;

Extracted by GlobalMSDS Ltd

- 12 March 2019
- (2) Install vertical elutriator in sampling locations specified above with inlet 4 1/2 to 5 1/2 feet from floor (breathing zone height);
- (3) Remove top section of cassette;
- (4) Install cassette in ferrule of elutriator;
- (5) Tape cassette to ferrule with masking tape or similar material for air-tight seal;
- (6) Remove bottom plug of cassette and attach hose containing critical orifice;
- (7) Start elutriator pump and check to see if gauge reads above 17 in. of Hg vacuum;
- (8) Record starting time, cassette number, and sampler number;
- (9) At end of sampling period stop pump and record time; and
- (10) Controls with each batch of samples collected, two additional filter cassettes should be subjected to exactly the same handling as the samples, except that they are not opened. These control filters should be weighed in the same manner as the sample filters.

Any difference in weight in the control filters would indicate that the procedure for handling sample filters may not be adequate and should be evaluated to ascertain the cause of the difference, whether and what necessary corrections must be made, and whether additional samples must be collected.

- (d) Shipping. The cassette with samples should be collected, along with the appropriate number of blanks, and shipped to the analytical laboratory in a suitable container to prevent damage in transit.
- (e) Weighing of the sample should be achieved as follows:
- (1) Remove shrink band;
- (2) Remove top and middle sections of cassette and bottom plug;
- (3) Remove filter from cassette and weigh to an accuracy of 10 ug; and
- (4) Record weight in log against original weight

- (f) Calculation of volume of air sampled should be determined as follows:
- (1) From starting and stopping times of sampling period, determine length of time in minutes of sampling period; and
- (2) Multiply sampling time in minutes by flow rate of critical orifice in liters per minute and divide by 1000 to find air quantity in cubic meters.
- (g) Calculation of Dust Concentrations should be made as follows:
- (1) Subtract weight of clean filter from dirty filter and apply control correction to find actual weight of sample. Record this weight (in ug) in log; and
- (2) Divide mass of sample in ug by air volume in cubic meters to find dust concentration in ug/m. Record in log.

Appendix B-1	
RESPIRAT	FORY QUESTIONNAIRE
A. IDENTIFICATION DATA	
PLANT	SOCIAL SECURITY NO.

Extracted by GlobalMSDS Ltd 12 March 2019

						(fig-	(last
						ures)	2
							dig-
							its)
NAME	DATE	OF	INTE	RVIEW .			
(Surname)							
	DATE	OF	BIRT	Н			
(First Names)							
					M	F	
ADDRESS	AGE _		(8,	9) SEX			(10)
		M		N	IND	OTHE	lR
	RACE						(11)
INTERVIEWER: 1 2 3 4	5	6	7	8			(12)
WORK SHIFT: 1st 2nd _	;	3rd		_			(13)
STANDING HEIGHT				_		(1	4, 15)
WEIGHT				_		(1	6, 18)

Extracted by GlobalMSDS Ltd 12 March 2019

If working in more than one specified work area, X area where most of the work shift is spent. If "other," but spending 25% of the work shift in one of the specified work areas, classify in that work area. If carding department employee, check area within that department where most of the work shift is spent (if in doubt, check "throughout"). For work areas such as spinning and weaving where many work rooms may be involved, be sure to check to specific work room to which the employee is assigned - if he works in more than one work room within a department classify as 7 (all) for that department.

Work-	(19)	(20)		(21) Card		(23)	(24)	(25)	
 Number	Open	Pick	Area	#1	#2	Spin	Wind	Twist	_
1									•
1				_ :	_ :	_ I	_	_1	_ & cotton
2 	 						 	 	T.
		l	 Comb	l	i I	 	 	 	
	 	 	 Rove	 	 	' 			•
			 Thru	I	1			 	
 	l I	l 	Out 	l 	l I	l 	 	l 	l
	 	 		 		 	 	 	l I

Extracted by GlobalMSDS Ltd

12 March	2019
----------	------

	l	.	l	l	l	l	l	l	l	
	l	I	l	l	l	l	l	I	l	
	7		l	l	l	l	l	l	I	l
	(all)	I	l	l	l	l	l	l	l	l
	_l	I	_1	_	_	_	_	_	_	_
		I	I	l	l	l	l	l	I	I
Control		I	1	1			1		1	
(synthe-	- 8	I	1	1		1	1		1	
tic &		1	l	l	l	l	l	l	l	l
wool)		I	l	l	l	l	l	l	l	l
	_		_1	_1	_	_	_	_	_	_
	l	I	I		l	l		I	I	l
Ex-		I	I	I		I	I		1	I
Worker	9	I	I	l	l	l	l	l	I	
(cotton)		I	1	1	1	I	I		I	
	l		I	l	l	l		l	I	l
	_	I	_1	_1	_	_	_1	_	_	_

Continued --

Work- (26) (27) (28) (29) (30)

room

Number Spool Warp Slash Weave Other

Extracted by GlobalMSDS Ltd 12 March 2019

12 IVIai	CII 2019					
						I
	4				- 1	1
	l	ll				1
					1	1
	5				1	1
					1	ı
		· ———— ·			·	·
					,	
					,	ı
	l					[
						I
	7				1	1
	(all)				1	1
	_	_1	_1	_1	_	
					1	1
Control		I	I	I		I I
(synthe-	- 8	I	I	I		I I
tic &	l				1	1
						'
wool)					,	1
		_				
						1
Ex-		1	1	1		1
Worker	9				1	I
(cotton)	1	I	I	I		1
	l				1	I
		I	I	I		I I
			- '	- '		

Use actual wording of each question. Put X in appropriate square after each question. When in doubt record `No'. When no square, circle appropriate answer.

Extracted by GlobalMSDS Ltd 12 March 2019

(on getting up) |

Do you usually cough first	Ĵ.			
thing in the morning? _				
		Yes	No	(31)
(Count a cough with firs	st			
smoke or on "first go:	ing out o	f		
doors." Exclude clear:	ing throa	t		
or a single cough.)				
Do you usually cough during	ng			
the day or at night?				
(Ignore an occasional co	ough.)	Yes	No	(32)
If `Yes' to either question	n (31-32)	:		
Do you cough like this on	most			
days for as much as thre	эe			
months a year?		Yes	No	(33)
Do you cough on any partic	cular			
day of the week?				
		Yes	No	(34)
(1)	(2) (3) (4) (5) (6) (7)
If `Yes': Which day? Mon	Tues W	ed Thur	Fri Sat S	un (35)

Extracted by GlobalMSDS Ltd 12 March 2019

If `Yes' to question (33) or (38):

C. PHLEGM or alternative word to suit	local custom		
^			
(on getting up)			
Do you usually bring up any			
phlegm from your chest first			
thing in the morning? (Count			
phlegm with the first smoke			
or on "first going out of			
doors." Exclude phlegm from			
the nose. Count swallowed phlegm.)			
	Yes	No	(36)
Do you usually bring up any			
phlegm from your chest during			
the day or at night?			
(Accept twice or more.)			
	Yes	No	(37)
If `Yes' to question (36) or (37):			
Do you bring up any phlegm like			
this on most days for as			
much as three months each year?	Yes	No	(38)

Extracted by GlobalMSDS Ltd 12 March 2019

(cough)	(1)	2 years or less	(39)				
How long have you had							
this phlegm?							
(Write in number of years)	(2)	More than 2 years	3				
		- 9 years					
	(3)	10-19 years					
	(4)	20+ years					
* These words are for subjects who	work at	night					
D. CHEST ILLNESSES							
In the past three years,	(1)	No	(40)				
have you had a period							
of (increased) *cough	(2)	Yes, only one					
and phlegm lasting for		period					
3 weeks or more?							
	(3)	Yes, two or more					
		periods					
*For subjects who usually have phl	Legm						
During the past 3 years have you had							
any chest illness which has kep	ot						
you off work, indoors at home or							

Extracted by GlobalMSDS Ltd

Lauracica	oy Globally BBB E
12 March	2019

in bed? (For as long as one wee	k,		
flu?)	Yes	No	(41)
If `Yes' to (41):			
Did you bring up (more) phlegm th	an		
usual in any of these illnesses	?		
	Voc	No	(42)
	163		(42)
If `Yes' to (42):			
During the past three years have			
you had:			
Only one such ill	ness		
with increased ph	legm?	(1)	(43)
More than one suc	h illness:	(2)	(44)
	Br	. Grade	
E. TIGHTNESS			
Does your chest ever feel tight o	r.		
your breathing become difficult	?		
	Yes	No	(45)
Is your chest tight or your breat difficult on any particular da			
arrited on any particular da	ays		

Extracted by GlobalMSDS Ltd

12	\mathbf{N}	[arch	20	10
12	IVI	aicii	ZU	リソ

from the mill)				_
	Yes		No	(46)
				_ (,
Yes': Which day? (3) (4)	(5)	(6)	(7) (8)	
Mon. ^ Tues. Wed.	Thur.	Fri.	Sat. Sun.	(47)
(1) / \ (2)				
Sometimes Always				
Yes' Monday At what time on				
Monday does your chest feel				
ight or your breathing difficult?				
(1)	Before e	enterir	ng the mill	(48)
(0)				
(2)	After en	itering	g the mill	
Ask only if NO to Question (45)				
In the past, has your chest ever				
been tight or your breathing				
difficult on any particular				
day of the week?				_
	Yes		No	(49)

Extracted by GlobalMSDS Ltd 12 March 2019

2 March 201	7								
	Mon.	^	Tues.	Wed.	Thur.	Fri.	Sat.	Sun.	(50)
	(1)	/	\ (2)						

Sometimes Always

F	BREZ	THLE	SSNESS

If disabled from walking by any			
condition other than heart or			
lung disease put "X" here and			
leave questions (52-60) unasked.			(51)
Are you ever troubled by			
shortness of breath, when			
hurrying on the level or			
walking up a slight hill?			
	Yes	No	(52)
	Yes	No	(52)
If `No', grade is 1.	Yes	No	(52)
<pre>If `No', grade is 1. If `Yes', proceed to next question.</pre>	Yes	No	(52)
-	Yes	No	(52)
-	Yes	No	(52)
If `Yes', proceed to next question.	Yes	No	(52)
If `Yes', proceed to next question. Do you get short of breath walking		No	(52)
If `Yes', proceed to next question. Do you get short of breath walking with other people at an ordinary		No	(52)
If `Yes', proceed to next question. Do you get short of breath walking with other people at an ordinary			

If `No', grade is 2.

If `Yes', proceed to next question.

Do you have to stop for breath

Extracted by GlobalMSDS Ltd 12 March 2019

1	when walking at your own pac	ce			
(on the level?		Yes	No	(54)
Ιf	`No', grade is 3.				
Ιf	`Yes', proceed to next quest	tion.			
Are	e you short of breath on				
7	washing or dressing?				
			Yes	No	(55)
Ιf	`No', grade is 4.				
Ιf	`Yes' grade is 5.				
		Dyspn	ea Grd		(56)
ON I	MONDAYS				
Are	e you ever troubled by short	tness			
(of breath, when hurrying on	the			
	level or walking up a slight	t hill	?		
			Yes	No	(57)
Ιf	`No', grade is 1.				
Ιf	Yes', proceed to next ques	tion.			
Do	you get short of breath was	lking			
ī	with other people at ordina:	ry			
]	pace on the level?				

Yes _____ No ____ (58)

Extracted by GlobalMSDS Ltd 12 March 2019

If `No', grade is 2.			
If `Yes', proceed to next quest	cion.		
Do you have to stop for breath	1		
when walking at your own pac	ce		
on level ground?			
	Yes	No	(59)
If `No', grade is 3.			
If `Yes', proceed to next quest	cion.		
Are you short of breath on was	shing		
or dressing?			
	Yes	No	(60)
If `No', grade is 4.			
If `Yes', grade is 5.			
	B. Grd		(61)
G. OTHER ILLNESSES AND ALLERGY	/ HISTORY		
Do you have a heart condition	for		
which you are under a doctor	r's care?		
	Yes	No	(62)
Have you ever had asthma?	Ves	No	(63)

Extracted by GlobalMSDS Ltd 12 March 2019

If `Yes', did it begin:	(1)	Before age	
	(2)	After age 3	0
If `Yes' before 30 did you have			
asthma before ever going to work			
in a textile mill?			
	Yes	No	(64)
Have you ever had hay fever or			
other allergies (other than ab	ove)?		
	Yes	No	(65)
H. TOBACCO SMOKING*			
Do you smoke?			
-			
Record `Yes', if regular smoke:	r up		
to one month ago (Cigarettes,			
or pipe)			
<u> </u>			
	Yes	No	(66)
If `No' to (63)			
Have you ever smoked? (Cigaret	tes,		
cigars, pipe. Record `No' if s			
has never smoked as much as one			
cigarette a day, or 1 oz of to			

Extracted by GlobalMSDS Ltd

12	Marcl	20	10
14	IVI aiCi	1 20	17

a mo:	nth,	for as	s long	as or	ne year	.)				
						Yes		_ No		_ (67)
If `	Yes'	to (63	3) or	(64),	what h	ave				
you	smoke	d and	for ho	ow mai	ny year	s?				
(Wri	te in	speci	ific nu	umber	of yea	rs				
in t	he ap	propri	iate so	quare)					
	(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	
	I	I	1		I	1	I	I		
Years	< 5	5-9	110-14	4 15-3	19 20-2	4 25-2	29 30-3	4 35-3	39 >40	1
	_1	_	_1	_			I	_	I	.
Cigar-	I	1	I			1	I	I	I	1
ettes	I	1	I		1		I	I	I	(68)
1	_	_	_	_	I	_	1	_	I	.
Pipe	I	1	I		1	1	I	1	I	(69)
1	_	_	_	_	I	_	1	_	I	.
Cigars	I	1	I			1	I	I	I	(70)
1	_	_	_1	_	I	_	I	_	I	.
If ciga	rette	s, how	w many	packs	s per d	ay?				
(Write	in n	umber	of c	igare	ttes)					
			(1)		Less t	han 1/	'2 pack			(71)
			(2)		1/2 pa	ck, bu	ıt less	than	1 pack	:
			(3)		1 pack	, but	less t	han 1	1/2	
					packs					
			(4)		1 1/2	packs	or mor	е		

Extracted by GlobalMSDS Ltd 12 March 2019

Number of years		(72, 73)
If an ex smoker (cigarettes, cigar		
or pipe), how long since you s		
topped? (Write in number of years)		(74)
(1) _	0-1 year	
(2)	1-4 years	
(3)	5-9 years	
(4)	10+ years	
* Have you changed your smoking		
habits since last interview?		
If yes, specify what changes.		
T OCCUPATIONAL HIGHODY++		
I. OCCUPATIONAL HISTORY**		
Have you ever worked in:		
A foundry? (As long as one year)		
	Yes No _	(75)
Stone or mineral mining, quarry		
or processing? (As long as one ye	ear)	
	Yes No _	(76)
	110	(70)
Asbestos milling or processing?		
	Yes No	(77)

Extracted by GlobalMSDS Ltd

12	Ma	rch	201	10
12	IVI	псп	201	19

Other dusts, fumes or smoke?	
If yes, specify	
Yes _	No (78)
Type of exposure	
Length of exposure	
** Ask only on first interview.	
At what age did you first go to work in a	textile mill?
(Write in specific age in appropriate squa	are)
(1) (2) (3) (4) (5)	(6)
	
1 1 1 1 1	I I
< 20 20-24 25-29 30-34 35-39	40+
111111	_II
1 1 1 1 1	I I
llllll	.
When you first worked in a textile mill,	lid you
work with:	
(1) Cotton or cotto	on blend (79)
(2) Synthetic or wo	001 (80)
Appendix B-II	
Respiratory Questionnais	re
For	

Non-Textile Workers for the

$\frac{https://www.osha.gov/laws-regs/regulations/standardnumber/1910/1910.1043}{Extracted by GlobalMSDS Ltd}$

12	2 March 2019 Cotton Industry					
Ide	entification No. Interviewer Code					
Loc	ation Date of Interview					
	A. IDENTIFICATION					
1.	NAME (Last) (First) (Middle Initial)					
2.	CURRENT ADDRESS (Number, Street, or Rural Route, City or Town, County, State, Zip Code)					
3.	PHONE NUMBER AREA CODE NO.					
4.	() SOCIAL SECURITY: (optional see below)					

Extracted by GlobalMSDS Ltd 12 March 2019

5.	BIRTHDATE (Mo., Day, Yr.)
6.	AGE LAST BIRTHDAY
7.	SEX
	1 Male 2 Female
8.	ETHNIC GROUP OR ANCESTRY
	1 White, not of Hispanic Origin
	2 Black, not of Hispanic Origin
	3 Hispanic
	4 American Indian or Alaskan Native
	5 Asian or Pacific Islander6 Other:
9.	STANDING HEIGHT
	(Cm)

Extracted by GlobalMSDS Ltd 12 March 2019

). WEIGHT	
. WORK SHIFT	
1st 2nd _	3rd
. PRESENT WORK AREA	
Please indicate prima	ary assigned work area and percent of
time spent at that s	ite. If at other locations, please
	rcent of time for each.
	I
PRIMARY WORK AREA	l
	I
SPECIFIC JOB	l
. APPROPRIATE INDUSTR	Υ
1 Garnetting	
2. Cottonseed	O;1 M;11

Extracted by GlobalMSDS Ltd 12 March 2019

3	Cotton Warehouse
4	Utilization
5	Cotton Classification
6	Cotton Ginning

(Furnishing your Social Security number is voluntary. Your refusal to provide this number will not affect any right, benefit, or privilege to which you would be entitled if you did provide your Social Security number. Your Social Security number is being requested since it will permit use in future determinations in statistical research studies.)

B. OCCUPATIONAL HISTORY TABLE

Complete the following table showing the entire work history of the individual from present to initial employment. Sporadic, part-time periods of employment, each of no significant duration, should be grouped if possible.

I	I	I	I
TEN	URE OF	AVERAG	E HAZARDOUS HEALTH
INDUSTRY EMP	LOYMENT SPEC	CIFIC NO.	EXPOSURE ASSOCIATED
AND	OCCUPA	ATION DAYS	WITH WORK
LOCATION	1 1	WORKE	D
FROM	I TO	PER	1 1
19	19	WEEK	YES NO IF YES,

Extracted by GlobalMSDS Ltd 12 March 2019 ____I___ ___|___|___|__ __|_ -___|__|__| ___I___ __|__|___| ____I ____|___ 1 1

C. SYMPTOMS

1 1

Extracted by GlobalMSDS Ltd 12 March 2019

after each question. When in doubt r	ecord "No.".
COUGH	
1. Do you usually cough first	
thing in the morning?	1 Yes 2 No
(on getting up) *	
(Count a cough with first	
smoke or on "first going	
out of doors". Exclude	
clearing throat or a single	
cough.)	
2. Do you usually cough during	1 Yes 2 No
the day or at night?	
(Ignore an occasional cough.)	
If YES to either 1 or 2:	
3. Do you cough like this on days	1 Yes 2 No
for as much as three months a	
year?	9. NA
4. Do you cough on any particular	1. Yes 2. No
day of the week?	
<u>.</u>	
If YES:	

5. Which day? Mon. Tue. Wed. Thur. Fri. Sat. Sun.

PHLEGM

Extracted by GlobalMSDS Ltd 12 March 2019

ó.	Do you usually bring up any	1	Yes	2	No
	phlegm from your chest first				
	thing in the morning? (on				
	getting up)* (Count phlegm				
	with the first smoke or on				
	"first going out of doors."				
	Exclude phlegm from the nose.				
	Count swallowed phlegm.				
7.	Do you usually bring up any	1	Yes	2	No
	phlegm from your chest during				
	the day or at night?				
	(Accept twice or more.)				
Ιſ	YES to either question 6 or 7:				
3.	Do you bring up phlegm like	1	Yes	2	No
	this on most days for as much				
	as three months each year?				
Ιf	YES to question 3 or 8:				
9.	How long have you had this phlegm?	(1)	_ 2 y	ears or 1	less
	(cough) (Write in number of years)				
		(2)	More	than 2	
			year	s - 9 yea	ars
		(3)	10-1	9 years	
		(4)	20+ 1	years	

Extracted by GlobalMSDS Ltd 12 March 2019

* These words are for subjects who				
work at night.				
CHEST ILLNESS				
10. In the past three years, have	(1)	_ No		
you had a period of (increased)				
cough and phlegm lasting for 3	(2)	Yes,	only on	е
weeks or more?		peri	od	
	(3)	Yes,	two or	
		more	periods	
For subjects who usually have phlegm:				
11. During the past 3 years have	1	Yes	2	No
you had any chest illness which				
has kept you off work, indoors at				
home or in bed?				
(For as long as one week, flu?)				
If YES to 11:				
12. Did you bring up (more) phlegm	1	Yes	2	No
than usual in any of these				
illnesses?				
If YES to 12: During the past three				
years have you had:				
13. Only one such illness with	1	Yes	2	No

Extracted by GlobalMSDS Ltd 12 March 2019

increased phlegm?

14. More than one such illness:	1 Yes 2 No
	Br. Grade
TIGHTNESS	
15. Does your chest ever feel tight or your breathing become difficult?	1 Yes 2 No
16. Is your chest tight or your breathing difficult on any particular day of the week? (after a week or 10 days away from the mill)	1 Yes 2 No
17. If `Yes': Which day? (3) Mon. ^ Tues. (1) / \ (2) Sometimes Always	(4) (5) (6) (7) (8) Wed. Thur. Fri. Sat. Sun.
18. If YES Monday: At what time on Monday does your chest feel tight or your breathing difficult?	Before entering mill After entering mill

(ASK ONLY IF NO TO QUESTION 15)

Extracted by GlobalMSDS Ltd 12 March 2019

101							
19. In the past		est		1	res	2	NC
	ight or your						
breathing d	ifficult on an	У					
particular o	day of the wee	k?					
20. If `Yes': V	Which day?	(3)	(4)	(5)	(6)	(7)	(8)
	Mon. ^	Tues.	Wed.	Thur.	Fri.	Sat.	Sun.
	(1) / \	(2)					
	Sometimes A	lways					
BREATHLESSNESS							
21. If disable	d from walking		_		_		
by any cond:	ition other						
than heart o	or lung diseas	е					
put "X" in 1	the space and						
leave quest:	ions (22-30)						
unasked.							
22. Are you eve	er troubled by		1		Yes	2	Nο
	f breath, when		_		100	- <u></u>	_ 110
	the level or						
1 3							
walking up a	a slight hill?						
If NO, grade is	s 1. If YES,						
proceed to m	next question.						
23. Do you get	short of brea	th	1	•	Yes	2	_ No
walking with	n other people						
at an ordina	ary pace on th	е					

Extracted by GlobalMSDS Ltd 12 March 2019

level?

Ιf	NO, grade is 2. If YES, proceed to next question.					
24.	Do you have to stop for		1	Yes	2	No
	breath when walking at					
	your own pace on the level?					
Ιf	NO, grade is 3. If YES,					
	proceed to next question.					
25.	Are you short of breath on		1	Yes	2	No
	washing or dressing?					
Ιf	NO, grade is 4, If YES,					
	grade is 5.					
26.		Dyspnea	Grd			
26.		Dyspnea	Grd			
26.		Dyspnea	Grd			
	MONDAYS:	Dyspnea	Grd			
		Dyspnea	Grd			
ON		Dyspnea	Grd	Yes	2	No
ON	MONDAYS:	Dyspnea	_		2	No
ON	MONDAYS: Are you ever troubled by	Dyspnea	_		2	No
ON	MONDAYS: Are you ever troubled by shortness of breath, when	Dyspnea	_		2	No
ON	MONDAYS: Are you ever troubled by shortness of breath, when hurrying on the level or	Dyspnea	_		2	No
ON 27.	MONDAYS: Are you ever troubled by shortness of breath, when hurrying on the level or	Dyspnea	_		2	No
ON 27.	MONDAYS: Are you ever troubled by shortness of breath, when hurrying on the level or walking up a slight hill?	Dyspnea	_		2	No
ON 27.	MONDAYS: Are you ever troubled by shortness of breath, when hurrying on the level or walking up a slight hill? NO, grade is 1, If YES,	Dyspnea	_		2	No
ON 27.	MONDAYS: Are you ever troubled by shortness of breath, when hurrying on the level or walking up a slight hill? NO, grade is 1, If YES,		1	Yes	2	
ON 27.	MONDAYS: Are you ever troubled by shortness of breath, when hurrying on the level or walking up a slight hill? NO, grade is 1, If YES, proceed to next question.		1	Yes		

Extracted by GlobalMSDS Ltd 12 March 2019

level?

If NO, grade is 2, If YES,				
proceed to next question.				
29. Do you have to stop for	1	Yes 2	2	No
breath when walking at				
your own pace on the level?				
If NO, grade is 3, If YES,				
proceed to next question.				
30. Are you short of breath	1	Yes 2	2 •	No
on washing or dressing?				
If NO, grade is 4, If YES,				
grade is 5.				
	B. Grd			
OTHER ILLNESSES AND ALLERGY HISTO	DV			
OTHER THEMESSES AND ALLERGI HISTO.	N1			
32. Do you have a heart	1.	Yes 2	2.	No
condition for which you	· 	_		
are under a doctor's care?				
33. Have you ever had asthma?	1	Yes 2	2 •	No
If yes, did it begin:				
	(1) Befo	ore age 3	30	
	(2) Afte	er age 30)	

Extracted by GlobalMSDS Ltd 12 March 2019

34. If yes before 30: did you	1	Yes	2	No
have asthma before ever				
going to work in a textile				
mill?				
35. Have you ever had hay fever	1	Yes	2	No
or other allergies (other				
than above)?				
FOBACCO SMOKING				
36. Do you smoke?	1	Yes	2	No
Record Yes if regular smoker				
up to one month ago.				
(Cigarettes, cigar or pipe)				
If NO to (33).				
37. Have you ever smoked?	1	Yes	2	No
(Cigarettes, cigars, pipe.				
Record NO if subject has never				
smoked as much as one cigarette				
a day, or 1 oz. of tobacco a				
month, for as long as one year.				
If YES to (33) or (34); what have you				
smoked for how many years?				
(Write in specific number of years				
in the appropriate square)				

Extracted by GlobalMSDS Ltd 12 March 2019

_							
	Years			10-14	 15-19	20-24	25-29
=			l	 	l	 	
38.	Cigarettes	I		I		I	I
-							
39.	Pipe		 			1	1
-		l	l	l	l	l	l
40.	Cigars					1	
-		l	l	l	l	l	l

[38, 39, 40 CONTINUED]

	Years	30-34	 35-39	>40
38.	Cigarettes	l 	 	
39.	Pipe	 	 	
40.	Cigars	 	 	

Extracted by GlobalMSDS Ltd 12 March 2019

. If cigarettes, how many pack	s per day?
Write in number of cigarettes	
	Less than 1/2 pack
	1/2 pack, but less than
	pack
	1 pack, but less than
	1 1/2 packs
	1-1/2 packs or more
Numbers of much seems	
. Number of pack years:	
. If an ex-smoker (Cigarettes,	
cigar or pipe), how long	
since you stopped?	
(Write in number of years.)	
	0-1 year
	1-4 years
	5-9 years
	10+ years

Extracted by GlobalMSDS Ltd 12 March 2019

Have you ever worked in:				
44. A foundry?	1	Yes	2	No
(As long as one year)				
45. Stone or mineral mining,	1	Yes	2	_ No
quarrying or processing?				
(As long as one year)				
46. Asbestos milling or	1	Yes	2	No
processing? (Ever)				
47. Cotton or cotton blend	1	Yes	2	No
mill? (For controls only)				
48. Other dusts, fumes or	1	Yes	2	No
smoke? If yes, specify.				
Type of exposure				
Length of exposure				
Appendix B-III				
ABBREVIATED RESPIRATOR	Y QUESTIC)NNAIR	E	
A. IDENTIFICATION DATA				
PLANT SOCIAL S	ECURITY N	10		
		DAY	MONTH	YEAR
			(fig-	(last

ures) 2

Extracted by GlobalMSDS Ltd 12 March 2019

					Ċ	lig-
					i	ts)
NAME	DATE	OF	INTERVIEW _			
(Surname)						
	DATE	OF	BIRTH			
(First Names)						
				М	F	
ADDRESS	AGE _		_ (8,9) SEX			_(10)
		W	N	IND	OTHER	
	RACE					_(11)
INTERVIEWER: 1 2 3 4	5	6	7 8			(12)
WORK SHIFT: 1st 2nd _	3	3rd				(13)
STANDING HEIGHT					(14,	15)
WEIGHT					(16,	18)

PRESENT WORK AREA

If working in more than one specified work area, X area where most of the work shift is spent. If "other," but spending 25% of the work shift in one of the specified work areas, classify in that work area. If carding department employee, check area within that department where most of the work shift is spent (if in doubt, check "throughout"). For work areas such as spinning and weaving where many

Extracted by GlobalMSDS Ltd 12 March 2019

work rooms may be involved, be sure to check to specific work room to which the employee is assigned - if he works in more than one work room within a department classify as 7 (all) for that department.

	Work-	(19)	(20)		(21)	(22)	(23)	(24)	(25)	
	room				Card					
	Number	Open	Pick	Area	#1	#2	Spin	Wind	Twist	
	I	l	I	I		l		l	I	I
AT RISK	1	I	I	Cards	5		I	ı	I	I
									1	& cotton
1							_			
blend)	2	1	1	Draw	I		1	1	I	I
	l	l	l	l	l	l	l	l	l	I
	I		I	I		l	l	l	I	I
	3		I	Comb		l			I	I
	l	l	l	l	l	l	l	l	l	I
	l		I	I		l			l	I
	4	l	I	Rove		l	I	l	I	I
	I	l	I	I		l		l	I	I
										I
	1 5	I	ı I	Thru		I			I	I
				Out				•	,	'
	1	I I	! !	ı		ı I		l I	I I	1
	' I	'	'	'	' ——— ı	'	'	' 	'	1
	6									
	l									
	l									
	7									
	(all)									
	_1									
	l									
Control		I	T	T	1		1	1	1	I

https://www.osha.gov/laws-regs/regulations/standardnumber/1910/1910.1043 Extracted by GlobalMSDS Ltd 12 March 2019 (synthe-| 8 | | | | | | | | |

tic &			I			l	I			I
wool)		I	I	I			I		I	I
	.	_I	_	_	_	_	_	_ _	_1	_
I		I	I	I			I		I	I
Ex-		I		I	I	T		1	I	
Worker	9			I			I		I	I
(cotton)		1		1	1	1		1	I	
I		I	I	I			I		I	I
	I	_	_	_	_	_	_ _	_ _	_ _	_

Continued --

Work- (26) (27) (28) (29) (30) room

Number Spool Warp Slash Weave Other

I I

AT RISK | 1 | | | | |

(cotton | ____| __| ___| & cotton | | | |

blend) | 2 | | | | | |

|____| 3 | | | | 1 - 1 | 4 | | 1 |____| | 5 | |

|____|__|__|

er/1910/1910.1043

Extracte			SDS I	Ltd			
12 Marc	h 2019						
- 1					l		
1	6						1
		I	ı	I	I	I	ı
'-							I
	7		I		l	l	
	(all)				l		
	ı	ı	1	1	1	ı	1
			_	_			_
			I				
ontrol	l						T
synthe-	8		1				1
ic &		l	I	I	I	I	I
wool)			I				
		_	_	_	_	_	_
-					l		
x-	l	ĺ	I	I	İ	1	ı
orker				I		l	
cotton)							T
-			I		l		I
	l	I	ı	ı	ı	ı	I
	. ———	-'	_'	- '	- '	- '	- '

square after each question. When in doubt record `No'. When no square, circle appropriate answer.

```
B. COUGH
       (on getting up) |
Do you usually cough first Yes \_ No \_ (31)
thing in the morning? _____
  (Count a cough with first smoke
  or on "first going out of
  doors." Exclude clearing throat
```

lnumber/1910/1910.1043

____(32)

https://www.osha.gov/laws-regs/re Extracted by GlobalMSDS Ltd 12 March 2019	<u>garacionis/s</u>	
or a single cough.)		
Do you usually cough during the	Yes	No
day or at night?		
(Ignore an occasional cough.)		
If `Yes' to either question		

*			
(31-32):			
Do you cough like this on	Yes	No	(33)
most days for as much as three			
months a year?			
Do you cough on any particular	Yes	No	(33)
day of the week?			

```
If `Yes': Which day? Mon Tues Wed Thur Fri Sat Sun (35)
```

(1) (2) (3) (4) (5) (6) (7)

C. PHLEGM or alternative word to suit local custom.

(on getting up) |

Do you usually bring up any phlegm from your chest first thing in the morning? (Count phlegm with the first

Extracted by GlobalMSDS Ltd 12 March 2019

smoke or on "first going out	
of doors." Exclude phlegm	
from the nose. Count	
swallowed phlegm.)	Yes No (36)
Do you usually bring up any	
phlegm from your chest during	
the day or at night?	
(Accept twice or more.)	Yes NO (37)
If `Yes' to question (36) or (37):	
Do you bring up phlegm like this	
on most days for as much as thr	ee
months each year?	Yes NO (38)
(cough)	(1) 2 years or less
(cough) How long have you had	(1) 2 years or less
	(1) 2 years or less
How long have you had	
How long have you had this phlegm?	
How long have you had this phlegm?	(2) More than 2 years
How long have you had this phlegm?	(2) More than 2 years
How long have you had this phlegm?	(2) More than 2 years - 9 years
How long have you had this phlegm?	(2) More than 2 years - 9 years
How long have you had this phlegm?	(2) More than 2 years - 9 years (3) 10-19 years
How long have you had this phlegm?	(2) More than 2 years - 9 years (3) 10-19 years (4) 20+ years

Extracted by GlobalMSDS Ltd 12 March 2019

Does your chest ever feel			
tight or your breathing			
become difficult?	Yes	No	(39)
Is your chest tight or your			
breathing difficult on any			
particular day of the week?			
(after a week or 10 days			
from the mill)	Yes	No	(40)
If `Yes': Which day? (3) (4)	(5) (6)	(7) (8)	
Mon. ^ Tues. Wed	. Thur. Fri.	Sat. Sun.	(41)
(1) / \ (2)			
Sometimes Always			
If `Yes' Monday: At what time			
on Monday does			
your chest feel			
tight or your			
breathing			
difficult?			
(1)	Before enteri	ng the mill	(42)
(2)	After enterin	ng the mill	
(Ask only if NO to Question (45)			
In the past, has your chest			
ever been tight or your			
breathing difficult on			
any particular day of the			

Extracted by GlobalMSDS Ltd 12 March 2019

week?	Yes	No	(43)

E. TOBACCO SMOKING

* Have you changed your smoking habits since last interview?

If yes, specify what changes.

APPENDIX C -- Spirometry Prediction Tables for Normal Males and Females

TABLE 1. PREDICTED FVC FOR MALES (KNUDSON, ET AL.:

AM. REV. RESPIR. DIS. 1976, 113, 587.)

AGE

HT	17	19	21	23	25	27	29	31	33	35
60.0	3.44	3.59	3.75	3.91	3.72	3.66	3.61	3.55	3.49	3.43
60.5	3.50	3.66	3.81	3.97	3.80	3.75	3.69	3.63	3.57	3.51
61.0	3.56	3.72	3.88	4.03	3.89	3.83	3.77	3.71	3.66	3.60
61.5	3.63	3.78	3.94	4.10	3.97	3.91	3.85	3.80	3.74	3.68
62.0	3.69	3.85	4.00	4.16	4.05	3.99	3.94	3.88	3.82	3.76
62.5	3.76	3.91	4.07	4.22	4.13	4.08	4.02	3.96	3.90	3.84
63.0	3.82	3.97	4.13	4.29	4.22	4.16	4.10	4.04	3.99	3.93
63.5	3.88	4.04	4.19	4.35	4.30	4.25	4.18	4.13	4.07	4.01
64.0	3.95	4.10	4.26	4.41	4.38	4.32	4.27	4.21	4.15	4.09
64.5	4.01	4.17	4.32	4.48	4.46	4.41	4.35	4.29	4.23	4.17
65.0	4.07	4.23	4.39	4.54	4.55	4.49	4.43	4.37	4.32	4.26
65.5	4.14	4.29	4.45	4.60	4.63	4.57	4.51	4.46	4.40	4.34

Extracted by GlobalMSDS Ltd

1	2	\mathbf{M}	arc	٦h	20	1	Q
1	4	IVI	aı٧	-11	~\	"	

12 M	arch 2	2019								
66.0	4.20	4.36	4.51	4.67	4.71	4.65	4.60	4.54	4.48	4.42
66.5	4.26	4.42	4.58	4.73	4.80	4.74	4.68	4.62	4.56	4.51
67.0	4.33	4.48	4.64	4.80	4.88	4.82	4.76	4.70	4.65	4.59
67.5	4.39	4.55	4.70	4.86	4.96	4.90	4.84	4.79	4.73	4.67
68.0	4.45	4.61	4.77	4.92	5.04	4.98	4.93	4.87	4.81	4.75
68.5	4.52	4.67	4.83	4.99	5.13	5.07	5.01	4.95	4.89	4.84
69.0	4.58	4.74	4.89	5.05	5.21	5.15	5.09	5.03	4.98	4.92
69.5	4.64	4.80	4.96	5.11	5.29	5.23	5.17	5.12	5.06	5.00
70.0	4.71	4.86	5.02	5.18	5.37	5.32	5.26	5.20	5.14	5.08
70.5	4.77	4.93	5.08	5.24	5.46	5.40	5.34	5.28	5.22	5.17
71.0	4.83	4.99	5.15	5.30	5.54	5.48	5.42	5.36	5.31	5.25
71.5	4.90	5.05	5.21	5.37	5.62	5.56	5.50	5.45	5.39	5.33
72.0	4.96	5.12	5.27	5.43	5.70	5.65	5.59	5.53	5.47	5.41
72.5	5.03	5.18	5.34	5.49	5.79	5.73	5.67	5.61	5.55	5.50
73.0	5.09	5.24	5.40	5.56	5.87	5.81	5.75	5.69	5.64	5.58
73.5	5.15	5.31	5.46	5.62	5.95	5.89	5.83	5.78	5.70	5.66
74.0	5.22	5.37	5.53	5.68	6.03	5.98	5.92	5.86	5.80	5.74
74.5	5.28	5.44	5.59	5.75	6.12	6.06	6.00	5.94	5.88	5.83
75.0	5.34	5.50	5.65	5.81	6.20	6.14	6.08	6.02	5.97	5.91
75.5	5.41	5.56	5.72	5.87	6.28	6.22	6.17	6.11	6.05	5.99
76.0	5.47	5.63	5.78	5.94	6.36	6.31	6.25	6.19	6.13	6.07
76.5	5.53	5.69	5.85	6.00	6.45	6.39	6.33	6.27	6.21	6.16
77.0	5.60	5.75	5.91	6.06	6.53	6.47	6.41	6.35	6.30	6.24
77.5	5.66	5.82	5.97	6.13	6.61	6.55	6.50	6.44	6.38	6.32
78.0	5.72	5.88	6.04	6.19	6.69	6.64	6.58	6.52	6.46	6.40
78.5	5.79	5.94	6.10	6.26	6.78	6.72	6.66	6.60	6.54	6.49
79.0	5.85	6.01	6.16	6.32	6.86	6.80	6.74	6.68	6.63	6.57
79.5	5.91	6.07	6.23	6.38	6.94	6.88	6.83	6.77	6.71	6.65
80.0	5.98	6.13	6.29	6.45	7.02	6.97	6.91	6.85	6.79	6.73
80.5	6.04	6.20	6.35	6.51	7.11	7.05	6.99	6.93	6.87	6.82
81.0	6.10	6.26	6.42	6.57	7.19	7.13	7.07	7.02	6.96	6.90
81.5	6.17	6.32	6.48	6.64	7.27	7.21	7.16	7.10	7.04	6.98
82.0	6.23	6.39	6.54	6.70	7.35	7.30	7.24	7.18	7.12	7.06
82.5	6.30	6.45	6.61	6.76	7.44	7.38	7.32	7.26	7.20	7.15

Extracted by GlobalMSDS Ltd

12 March 2019

83.0	6.36	6.51	6.67	6.83	7.52	7.46	7.40	7.35	7.29	7.23
83.5	6.42	6.58	6.73	6.89	7.60	7.54	7.49	7.43	7.37	7.31
84.0	6.49	6.64	6.80	6.95	7.68	7.63	7.57	7.51	7.45	7.39
84.5	6.55	6.71	6.86	7.02	7.77	7.71	7.65	7.59	7.53	7.48
85.0	6.61	6.77	6.92	7.08	7.85	7.79	7.73	7.68	7.62	7.56

APPENDIX C -- Spirometry Prediction Tables for Normal Males and Females (Continued)

TABLE 1. PREDICTED FVC FOR MALES (KNUDSON, ET AL.:

AM. REV. RESPIR. DIS. 1976, 113, 587.)

AGE

HT	37	39	41	43	45	47	49	51
60.0	3.37	3.32	3.26	3.20	3.14	3.08	3.03	2.97
60.5	3.46	3.40	3.34	3.28	3.22	3.17	3.11	3.05
61.0	3.54	3.48	3.42	3.37	3.31	3.25	3.19	3.13
61.5	3.62	3.56	3.51	3.45	3.39	3.33	3.27	3.22
62.0	3.70	3.65	3.59	3.53	3.47	3.41	3.36	3.30
62.5	3.79	3.73	3.67	3.61	3.55	3.50	3.44	3.38
63.0	3.87	3.81	3.75	3.70	3.64	3.58	3.52	3.46
63.5	3.95	3.89	3.84	3.78	3.72	3.66	3.60	3.55
64.0	4.03	3.98	3.92	3.86	3.80	3.74	3.69	3.63
64.5	4.12	4.06	4.00	3.94	3.88	3.83	3.77	3.71
65.0	4.20	4.14	4.08	4.03	3.97	3.91	3.85	3.79
65.5	4.28	4.22	4.17	4.11	4.05	3.99	3.93	3.88
66.0	4.36	4.31	4.25	4.19	4.13	4.07	4.02	3.96
66.5	4.45	4.39	4.33	4.27	4.22	4.16	4.10	4.04
67.0	4.53	4.47	4.41	4.36	4.30	4.24	4.18	4.12
67.5	4.61	4.55	4.50	4.44	4.38	4.32	4.26	4.21
68.0	4.69	4.64	4.58	4.52	4.46	4.40	4.35	4.29

Extracted by GlobalMSDS Ltd

12 March	2019)
----------	------	---

68.5	4.78	4.72	4.66	4.60	4.55	4.49	4.43	4.37
69.0	4.86	4.80	4.74	4.69	4.63	4.57	4.51	4.45
69.5	4.94	4.88	4.83	4.77	4.71	4.65	4.59	4.54
70.0	5.02	4.97	4.91	4.85	4.79	4.74	4.68	4.62
70.5	5.11	5.05	4.99	4.93	4.88	4.82	4.76	4.70
71.0	5.19	5.13	5.07	5.02	4.96	4.90	4.84	4.78
71.5	5.27	5.21	5.16	5.10	5.04	4.98	4.92	4.87
72.0	5.36	5.30	5.24	5.18	5.12	5.07	5.01	4.95
72.5	5.44	5.38	5.32	5.26	5.21	5.15	5.09	5.03
73.0	5.52	5.46	5.40	5.35	5.29	5.23	5.17	5.11
73.5	5.60	5.54	5.49	5.43	5.37	5.31	5.25	5.20
74.0	5.69	5.63	5.57	5.51	5.45	5.40	5.34	5.28
74.5	5.77	5.71	5.65	5.59	5.54	5.48	5.42	5.36
75.0	5.85	5.79	5.73	5.68	5.62	5.56	5.50	5.44
75.5	5.93	5.88	5.82	5.76	5.70	5.64	5.59	5.53
76.0	6.02	5.96	5.90	5.84	5.78	5.73	5.67	5.61
76.5	6.10	6.04	5.98	5.92	5.87	5.81	5.75	5.69
77.0	6.18	6.12	6.06	6.01	5.95	5.89	5.83	5.77
77.5	6.26	6.21	6.15	6.09	6.03	5.97	5.92	5.86
78.0	6.35	6.29	6.23	6.17	6.11	6.06	6.00	5.94
78.5	6.43	6.37	6.31	6.25	6.20	6.14	6.08	6.02
79.0	6.51	6.45	6.39	6.34	6.28	6.22	6.16	6.10
79.5	6.59	6.54	6.48	6.42	6.36	6.30	6.25	6.19
80.0	6.68	6.62	6.56	6.50	6.44	6.39	6.33	6.27
80.5	6.76	6.70	6.64	6.58	6.53	6.47	6.41	6.35
81.0	6.84	6.78	6.73	6.67	6.61	6.55	6.49	6.44
81.5	6.92	6.87	6.81	6.75	6.69	6.63	6.58	6.52
82.0	7.01	6.95	6.89	6.83	6.77	6.72	6.66	6.60
82.5	7.09	7.03	6.97	6.91	6.86	6.80	6.74	6.68
83.0	7.17	7.11	7.06	7.00	6.94	6.88	6.82	6.77
83.5	7.25	7.20	7.14	7.08	7.02	6.96	6.91	6.85
84.0	7.34	7.28	7.22	7.16	7.10	7.05	6.99	6.93
84.5	7.42	7.36	7.30	7.24	7.19	7.13	7.07	7.01
85.0	7.50	7.44	7.39	7.33	7.27	7.21	7.15	7.10

Extracted by GlobalMSDS Ltd 12 March 2019

APPENDIX C -- Spirometry Prediction Tables for Normal Males and Females (Continued)

TABLE 1. PREDICTED FVC FOR MALES (KNUDSON, ET AL.:

AM. REV. RESPIR. DIS. 1976, 113, 587.)

AGE

HT	53	55	57	59	61	63	65
60.0	2.91	2.85	2.79	2.74	2.68	2.62	2.56
60.5	2.99	2.93	2.88	2.82	2.76	2.70	2.64
61.0	3.08	3.02	2.96	2.90	2.84	2.79	2.73
61.5	3.16	3.10	3.04	2.98	2.93	2.87	2.81
62.0	3.24	3.18	3.12	3.07	3.01	2.95	2.89
62.5	3.32	3.26	3.21	3.15	3.09	3.03	2.97
63.0	3.41	3.35	3.29	3.23	3.17	3.12	3.06
63.5	3.49	3.43	3.37	3.31	3.26	3.20	3.14
64.0	3.57	3.51	3.45	3.40	3.34	3.28	3.22
64.5	3.65	3.59	3.54	3.48	3.42	3.36	3.30
65.0	3.74	3.68	3.62	3.56	3.50	3.45	3.39
65.5	3.82	3.76	3.70	3.64	3.59	3.53	3.47
66.0	3.90	3.84	3.78	3.73	3.67	3.61	3.55
66.5	3.98	3.93	3.87	3.81	3.75	3.69	3.64
67.0	4.07	4.01	3.95	3.89	3.83	3.78	3.72
67.5	4.15	4.09	4.03	3.97	3.92	3.86	3.80
68.0	4.23	4.17	4.11	4.06	4.00	3.94	3.88
68.5	4.31	4.26	4.20	4.14	4.08	4.02	3.97
69.0	4.40	4.34	4.28	4.22	4.16	4.11	4.05
69.5	4.48	4.42	4.36	4.30	4.25	4.19	4.13
70.0	4.56	4.50	4.44	4.39	4.33	4.27	4.21

Extracted by GlobalMSDS Ltd

12 March 2019

70.5	4.64	4.59	4.53	4.47	4.41	4.35	4.30
71.0	4.73	4.67	4.61	4.55	4.49	4.44	4.38
71.5	4.81	4.75	4.69	4.63	4.58	4.52	4.46
72.0	4.89	4.83	4.78	4.72	4.66	4.60	4.54
72.5	4.97	4.92	4.86	4.80	4.74	4.68	4.63
73.0	5.06	5.00	4.94	4.88	4.82	4.77	4.71
73.5	5.14	5.08	5.02	4.96	4.91	4.85	4.79
74.0	5.22	5.16	5.11	5.05	4.99	4.93	4.87
74.5	5.30	5.25	5.19	5.13	5.07	5.01	4.96
75.0	5.39	5.33	5.27	5.21	5.15	5.10	5.04
75.5	5.47	5.41	5.35	5.30	5.24	5.18	5.12
76.0	5.55	5.49	5.44	5.38	5.32	5.26	5.20
76.5	5.63	5.58	5.52	5.46	5.40	5.34	5.29
77.0	5.72	5.66	5.60	5.54	5.48	5.43	5.37
77.5	5.80	5.74	5.68	5.63	5.57	5.51	5.45
78.0	5.88	5.82	5.77	5.71	5.65	5.59	5.53
78.5	5.96	5.91	5.85	5.79	5.73	5.67	5.62
79.0	6.05	5.99	5.93	5.87	5.81	5.76	5.70
79.5	6.13	6.07	6.01	5.96	5.90	5.84	5.78
80.0	6.21	6.15	6.10	6.04	5.98	5.92	5.86
80.5	6.29	6.24	6.18	6.12	6.06	6.00	5.95
81.0	6.38	6.32	6.26	6.20	6.15	6.09	6.03
81.5	6.46	6.40	6.34	6.29	6.23	6.17	6.11
82.0	6.54	6.48	6.43	6.37	6.31	6.25	6.19
82.5	6.62	6.57	6.51	6.45	6.39	6.33	6.28
83.0	6.71	6.65	6.59	6.53	6.48	6.42	6.36
83.5	6.79	6.73	6.67	6.62	6.56	6.50	6.44
84.0	6.87	6.81	6.76	6.70	6.64	6.58	6.52
84.5	6.95	6.90	6.84	6.78	6.72	6.66	6.61
85.0	7.04	6.98	6.92	6.86	6.81	6.75	6.69

 ${\tt APPENDIX} \ {\tt C} \ {\tt --} \ {\tt Spirometry} \ {\tt Prediction} \ {\tt Tables} \ {\tt for} \ {\tt Normal} \ {\tt Males}$

Extracted by GlobalMSDS Ltd 12 March 2019

TABLE 2. PREDICTED FEV(1) FOR MALES (KNUDSON. ET AL.:

AM. REV. RESPIR. DIS. 1976, 113, 587.)

	AGE									
НТ	17	19	21	23	25	27	29	31	33	35
60.0	2.97	3.06	3.15	3.24	3.05	2.99	2.94	2.88	2.83	2.78
60.5	3.03	3.12	3.21	3.30	3.11	3.06	3.00	2.95	2.90	2.84
61.0	3.08	3.17	3.26	3.35	3.18	3.12	3.07	3.02	2.96	2.91
61.5	3.14	3.23	3.32	3.41	3.24	3.19	3.14	3.08	3.03	2.97
62.0	3.20	3.29	3.38	3.47	3.31	3.26	3.20	3.15	3.09	3.04
62.5	3.26	3.35	3.44	3.53	3.38	3.32	3.27	3.22	3.16	3.11
63.0	3.32	3.41	3.50	3.59	3.44	3.39	3.34	3.28	3.23	3.17
63.5	3.38	3.47	3.56	3.65	3.51	3.46	3.40	3.35	3.29	3.24
64.0	3.43	3.52	3.61	3.70	3.58	3.52	3.47	3.41	3.36	3.31
64.5	3.49	3.58	3.67	3.76	3.64	3.59	3.53	3.48	3.43	3.37
65.0	3.55	3.64	3.73	3.82	3.71	3.65	3.60	3.55	3.49	3.44
65.5	3.61	3.70	3.79	3.88	3.77	3.72	3.67	3.61	3.56	3.50
66.0	3.67	3.76	3.85	3.94	3.84	3.79	3.73	3.68	3.62	3.57
66.5	3.73	3.82	3.91	4.00	3.91	3.85	3.80	3.74	3.69	3.64
67.0	3.79	3.88	3.97	4.06	3.97	3.92	3.86	3.81	3.76	3.70
67.5	3.84	3.93	4.02	4.11	4.04	3.98	3.93	3.88	3.82	3.77
68.0	3.90	3.99	4.08	4.17	4.10	4.05	4.00	3.94	3.89	3.83
68.5	3.96	4.05	4.14	4.23	4.17	4.12	4.06	4.01	3.95	3.90
69.0	4.02	4.11	4.20	4.29	4.24	4.18	4.13	4.07	4.02	3.97
69.5	4.08	4.17	4.26	4.35	4.30	4.25	4.19	4.14	4.09	4.03
70.0	4.14	4.23	4.32	4.41	4.37	4.31	4.26	4.21	4.15	4.10
70.5	4.19	4.28	4.37	4.46	4.43	4.38	4.33	4.27	4.22	4.16
71.0	4.25	4.34	4.43	4.52	4.50	4.45	4.39	4.34	4.28	4.23
71.5	4.31	4.40	4.49	4.58	4.57	4.51	4.46	4.40	4.35	4.30
72.0	4.37	4.46	4.55	4.64	4.63	4.58	4.52	4.47	4.42	4.36
72.5	4.43	4.52	4.61	4.70	4.70	4.64	4.59	4.54	4.48	4.43
73.0	4.49	4.58	4.67	4.76	4.76	4.71	4.66	4.60	4.55	4.49
73.5	4.54	4.63	4.72	4.81	4.83	4.78	4.72	4.67	4.61	4.56

Extracted by GlobalMSDS Ltd

12 March 2019

1 2 1 1 1	aich 2	.017								
74.0	4.60	4.69	4.78	4.87	4.90	4.84	4.79	4.73	4.68	4.63
74.5	4.66	4.75	4.84	4.93	4.96	4.91	4.85	4.80	4.75	4.69
75.0	4.72	4.81	4.90	4.99	5.03	4.97	4.92	4.87	4.81	4.76
75.5	4.78	4.87	4.96	5.05	5.09	5.04	4.99	4.93	4.88	4.82
76.0	4.84	4.93	5.02	5.11	5.16	5.11	5.05	5.00	4.94	4.89
76.5	4.90	4.99	5.08	5.17	5.23	5.17	5.12	5.06	5.01	4.96
77.0	4.95	5.04	5.13	5.22	5.29	5.24	5.18	5.13	5.08	5.02
77.5	5.01	5.10	5.19	5.28	5.36	5.30	5.25	5.20	5.14	5.09
78.0	5.07	5.16	5.25	5.34	5.42	5.37	5.32	5.26	5.21	5.15
78.5	5.13	5.22	5.31	5.40	5.49	5.44	5.38	5.33	5.27	5.22
79.0	5.19	5.28	5.37	5.46	5.56	5.50	5.45	5.39	5.34	5.29
79.5	5.25	5.34	5.43	5.52	5.62	5.57	5.51	5.46	5.41	5.35
80.0	5.30	5.39	5.48	5.57	5.69	5.63	5.58	5.53	5.47	5.42
80.5	5.36	5.45	5.54	5.63	5.75	5.70	5.65	5.59	5.54	5.48
81.0	5.42	5.51	5.60	5.69	5.82	5.77	5.71	5.66	5.60	5.55
81.5	5.48	5.57	5.66	5.75	5.89	5.83	5.78	5.72	5.67	5.62
82.0	5.54	5.63	5.72	5.81	5.95	5.90	5.84	5.79	5.74	5.68
82.5	5.60	5.69	5.78	5.87	6.02	5.96	5.91	5.86	5.80	5.75
83.0	5.65	5.74	5.83	5.92	6.08	6.03	5.98	5.92	5.87	5.81
83.5	5.71	5.80	5.90	5.98	6.15	6.10	6.04	5.99	5.93	5.88
84.0	5.77	5.86	5.95	6.04	6.22	6.16	6.11	6.05	6.00	5.95
84.5	5.83	5.92	6.01	6.10	6.28	6.23	6.12	6.17	6.07	6.01
85.0	5.89	5.98	6.07	6.16	6.36	6.29	6.24	6.19	6.13	6.06

APPENDIX C -- Spirometry Prediction Tables for Normal Males and Females (Continued)

TABLE 2. PREDICTED FEV(1) FOR MALES (KNUDSON. ET AL.:

AM. REV. RESPIR. DIS. 1976, 113, 587.)

Extracted by GlobalMSDS Ltd

12 March 2019

1 2 101	iaicii 2	2017						
	AGE							
HT	37	39	41	43	45	47	49	51
60.0	2.72	2.67	2.61	2.56	2.51	2.45	2.40	2.34
60.5	2.79	2.73	2.68	2.63	2.57	2.52	2.46	2.41
61.0	2.85	2.80	2.75	2.69	2.64	2.58	2.53	2.48
61.5	2.92	2.87	2.81	2.76	2.70	2.65	2.60	2.54
62.0	2.99	2.93	2.88	2.82	2.77	2.72	2.66	2.61
62.5	3.05	3.00	2.95	2.89	2.84	2.78	2.73	2.68
63.0	3.12	3.07	3.01	2.96	2.90	2.85	2.80	2.74
63.5	3.19	3.13	3.08	3.02	2.97	2.92	2.86	2.81
64.0	3.25	3.20	3.14	3.09	3.04	2.98	2.93	2.87
64.5	3.32	3.26	3.21	3.16	3.10	3.05	2.99	2.94
65.0	3.38	3.33	3.28	3.22	3.17	3.11	3.06	3.01
65.5	3.45	3.40	3.34	3.29	3.23	3.18	3.13	3.07
66.0	3.52	3.46	3.41	3.35	3.30	3.25	3.19	3.14
66.5	3.58	3.53	3.47	3.42	3.37	3.31	3.26	3.20
67.0	3.65	3.59	3.54	3.49	3.43	3.38	3.32	3.27
67.5	3.71	3.66	3.61	3.55	3.50	3.44	3.39	3.34
68.0	3.78	3.73	3.67	3.62	3.56	3.51	3.46	3.40
68.5	3.85	3.79	3.74	3.68	3.63	3.58	3.52	3.47
69.0	3.91	3.86	3.80	3.75	3.70	3.64	3.59	3.53
69.5	3.98	3.92	3.87	3.82	3.76	3.71	3.65	3.60
70.0	4.04	3.99	3.94	3.88	3.83	3.77	3.72	3.67
70.5	4.11	4.06	4.00	3.95	3.89	3.84	3.79	3.73
71.0	4.18	4.12	4.07	4.01	3.96	3.91	3.85	3.80
71.5	4.24	4.19	4.13	4.08	4.03	3.97	3.92	3.86
72.0	4.31	4.25	4.20	4.15	4.09	4.04	3.98	3.93
72.5	4.37	4.32	4.27	4.21	4.16	4.10	4.05	4.00
73.0	4.44	4.39	4.33	4.28	4.22	4.17	4.12	4.06
73.5	4.51	4.45	4.40	4.34	4.29	4.24	4.18	4.13
74.0	4.57	4.52	4.46	4.41	4.36	4.30	4.25	4.19
74.5	4.64	4.58	4.53	4.48	4.42	4.37	4.31	4.26
75.0	4.70	4.65	4.60	4.54	4.49	4.43	4.38	4.33
75.5	4.77	4.72	4.66	4.61	4.55	4.50	4.45	4.39

Extracted by GlobalMSDS Ltd

12 March 2019

76.0	4.84	4.78	4.73	4.67	4.62	4.57	4.51	4.46
76.5	4.90	4.85	4.79	4.74	4.69	4.63	4.58	4.52
77.0	4.97	4.91	4.86	4.81	4.75	4.70	4.64	4.59
77.5	5.03	4.98	4.93	4.87	4.82	4.76	4.71	4.66
78.0	5.10	5.05	4.99	4.94	4.88	4.83	4.78	4.72
78.5	5.17	5.11	5.06	5.00	4.95	4.90	4.84	4.79
79.0	5.23	5.18	5.12	5.07	5.02	4.96	4.91	4.85
79.5	5.30	5.24	5.19	5.14	5.08	5.03	4.97	4.92
80.0	5.36	5.31	5.26	5.20	5.15	5.09	5.04	4.99
80.5	5.43	5.38	5.32	5.27	5.21	5.16	5.11	5.05
81.0	5.50	5.44	5.39	5.33	5.28	5.23	5.17	5.12
81.5	5.56	5.51	5.45	5.40	5.35	5.29	5.24	5.18
82.0	5.63	5.57	5.52	5.47	5.41	5.36	5.30	5.25
82.5	5.69	6.64	5.59	5.53	5.48	5.42	5.37	5.32
83.0	5.76	5.71	5.65	5.60	5.54	5.49	5.44	5.38
83.5	5.83	5.77	5.72	5.66	5.61	5.56	5.50	5.45
84.0	5.89	5.84	5.78	5.73	5.68	5.62	5.57	5.51
84.5	5.96	5.90	5.85	5.80	5.74	5.69	5.63	5.58
85.0	6.02	5.97	5.92	5.86	5.81	5.75	5.70	5.65

APPENDIX C -- Spirometry Prediction Tables for Normal Males and Females (Continued)

TABLE 2. PREDICTED FEV(1) FOR MALES (KNUDSON. ET AL.:

AM. REV. RESPIR. DIS. 1976, 113, 587.)

AGE

HT	53	55	57	59	61	63	65
60.0	2.29	2.24	2.18	2.13	2.07	2.02	1.97
60.5	2.36	2.30	2.25	2.19	2.14	2.09	2.03
61.0	2.42	2.37	2.31	2.26	2.21	2.15	2.10

Extracted by GlobalMSDS Ltd

1	\sim	TA /	г	1	-	119
	,	11/	191	'n	71	пч
	_	1 1	ш	\sim 11	~\	,,,

61.5	2.49	2.43	2.38	2.33	2.27	2.22	2.16
62.0	2.55	2.50	2.45	2.39	2.34	2.28	2.23
62.5	2.62	2.57	2.51	2.46	2.41	2.35	2.30
63.0	2.69	2.63	2.58	2.53	2.47	2.42	2.36
63.5	2.75	2.70	2.65	2.59	2.54	2.48	2.43
64.0	2.82	2.77	2.71	2.66	2.60	2.55	2.50
64.5	2.89	2.83	2.78	2.72	2.67	2.62	2.56
65.0	2.95	2.90	2.84	2.79	2.74	2.68	2.63
65.5	3.02	2.96	2.91	2.86	2.80	2.75	2.69
66.0	3.08	3.03	2.98	2.92	2.87	2.81	2.76
66.5	3.15	3.10	3.04	2.99	2.93	2.88	2.83
67.0	3.22	3.16	3.11	3.05	3.00	2.95	2.89
67.5	3.28	3.23	3.17	3.12	3.07	3.01	2.96
68.0	3.35	3.29	3.24	3.19	3.13	3.08	3.02
68.5	3.41	3.36	3.31	3.25	3.20	3.14	3.09
69.0	3.48	3.43	3.37	3.32	3.26	3.21	3.16
69.5	3.55	3.49	3.44	3.38	3.33	3.28	3.22
70.0	3.61	3.56	3.50	3.45	3.40	3.34	3.29
70.5	3.68	3.62	3.57	3.52	3.46	3.41	3.35
71.0	3.74	3.69	3.64	3.58	3.53	3.47	3.42
71.5	3.81	3.76	3.70	3.65	3.59	3.54	3.49
72.0	3.88	3.82	3.77	3.71	3.66	3.61	3.55
72.5	3.94	3.89	3.83	3.78	3.73	3.67	3.62
73.0	4.01	3.95	3.90	3.85	3.79	3.74	3.68
73.5	4.07	4.02	3.97	3.91	3.86	3.80	3.75
74.0	4.14	4.09	4.03	3.98	3.92	3.87	3.82
74.5	4.21	4.15	4.10	4.04	3.99	3.94	3.88
75.0	4.27	4.22	4.16	4.11	4.06	4.00	3.95
75.5	4.34	4.28	4.23	4.18	4.12	4.07	4.01
76.0	4.40	4.35	4.30	4.24	4.19	4.13	4.08
76.5	4.47	4.42	4.36	4.31	4.25	4.20	4.15
77.0	4.54	4.48	4.43	4.37	4.32	4.27	4.21
77.5	4.60	4.55	4.49	4.44	4.39	4.33	4.28
78.0	4.67	4.61	4.56	4.51	4.45	4.40	4.34

Extracted by GlobalMSDS Ltd

12 March 2019

78.5	4.73	4.68	4.63	4.57	4.52	4.46	4.41
79.0	4.80	4.75	4.69	4.64	4.58	4.53	4.48
79.5	4.87	4.81	4.76	4.70	4.65	4.60	4.54
80.0	4.93	4.88	4.82	4.77	4.72	4.66	4.61
80.5	5.00	4.94	4.89	4.84	4.78	4.73	4.67
81.0	5.06	5.01	4.96	4.90	4.85	4.79	4.74
81.5	5.13	5.08	5.02	4.97	4.91	4.86	4.81
82.0	5.20	5.14	5.09	5.03	4.98	4.93	4.87
82.5	5.26	5.21	5.15	5.10	5.05	4.99	4.94
83.0	5.33	5.27	5.22	5.17	5.11	5.06	5.00
83.5	5.39	5.34	5.29	5.23	5.18	5.12	5.07
84.0	5.46	5.41	5.35	5.30	5.24	5.19	5.14
84.5	5.53	5.47	5.42	5.36	5.31	5.26	5.20
85.0	5.59	5.54	5.58	5.43	5.38	5.32	5.27

APPENDIX C -- Spirometry Prediction Tables for Normal $\label{eq:males} \text{Males and Females}$

TABLE 3. PREDICTED FVC FOR FEMALES (KNUDSON, ET AL.:

AM. REV. RESPIR. DIS. 1976, 113, 587.)

AGE

HT	17	19	21	23	25	27	29	31	33	35
52.0	2.45	2.64	2.65	2.61	2.56	2.52	2.47	2.43	2.39	2.34
52.5	2.50	2.68	2.70	2.65	2.61	2.57	2.52	2.48	2.43	2.39
53.0	2.54	2.72	2.74	2.70	2.66	2.61	2.57	2.52	2.48	2.44
53.5	2.58	2.76	2.79	2.75	2.70	2.66	2.62	2.57	2.53	2.48
54.0	2.62	2.81	2.84	2.79	2.75	2.71	2.66	2.62	2.57	2.53
54.5	2.66	2.85	2.89	2.84	2.80	2.75	2.71	2.67	2.62	2.58
55.0	2.71	2.89	2.93	2.89	2.84	2.80	2.76	2.71	2.67	2.62
55.5	2.75	2.93	2.98	2.94	2.89	2.85	2.80	2.76	2.72	2.67
56.0	2.79	2.97	3.03	2.98	2.94	2.89	2.85	2.81	2.76	2.72
56.5	2.83	3.01	3.07	3.03	2.99	2.94	2.90	2.85	2.81	2.77

Extracted by GlobalMSDS Ltd

1	2	М	arch	20	110
1	_	TAT	arcı	120	ルファ

12 M	larch 2	2019								
57.0	2.87	3.06	3.12	3.08	3.03	2.99	2.94	2.90	2.86	2.81
57.5	2.91	3.10	3.17	3.12	3.08	3.04	2.99	2.95	2.90	2.86
58.0	2.96	3.14	3.21	3.17	3.13	3.08	3.04	2.99	2.95	2.91
58.5	3.00	3.18	3.26	3.22	3.17	3.13	3.09	3.04	3.00	2.95
59.0	3.04	3.22	3.31	3.26	3.22	3.18	3.13	3.09	3.04	3.00
59.5	3.08	3.27	3.36	3.31	3.27	3.22	3.18	3.14	3.09	3.05
60.0	3.12	3.31	3.40	3.36	3.31	3.27	3.23	3.18	3.14	3.09
60.5	3.17	3.35	3.45	3.41	3.36	3.32	3.27	3.23	3.19	3.14
61.0	3.21	3.39	3.50	3.45	3.41	3.36	3.32	3.28	3.23	3.19
61.5	3.25	3.43	3.54	3.50	3.46	3.41	3.37	3.32	3.28	3.24
62.0	3.29	3.48	3.59	3.55	3.50	3.46	3.41	3.37	3.33	3.28
62.5	3.33	3.52	3.64	3.59	3.55	3.51	3.46	3.42	3.37	3.33
63.0	3.38	3.56	3.68	3.64	3.60	3.55	3.51	3.46	3.42	3.38
63.5	3.42	3.60	3.73	3.69	3.64	3.60	3.56	3.51	3.47	3.42
64.0	3.46	3.64	3.78	3.73	3.69	3.65	3.60	3.56	3.51	3.47
64.5	3.50	3.69	3.83	3.78	3.74	3.69	3.65	3.61	3.56	3.52
65.0	3.54	3.73	3.87	3.83	3.78	3.74	3.70	3.65	3.61	3.56
65.5	3.59	3.77	3.92	3.88	3.83	3.79	3.74	3.70	3.66	3.61
66.0	3.63	3.81	3.97	3.92	3.88	3.83	3.79	3.75	3.70	3.66
66.5	3.67	3.85	4.01	3.97	3.93	3.88	3.84	3.79	3.75	3.71
67.0	3.71	3.89	4.06	4.02	3.97	3.93	3.88	3.84	3.80	3.75
67.5	3.75	3.94	4.11	4.06	4.02	3.98	3.93	3.89	3.84	3.80
68.0	3.79	3.98	4.15	4.11	4.07	4.02	3.98	3.93	3.89	3.85
68.5	3.84	4.02	4.20	4.16	4.11	4.07	4.03	3.98	3.94	3.89
69.0	3.88	4.06	4.25	4.20	4.16	4.12	4.07	4.03	3.98	3.94
69.5	3.92	4.10	4.30	4.29	4.21	4.16	4.12	4.08	4.03	3.99
70.0	3.96	4.15	4.34	4.30	4.25	4.21	4.17	4.12	4.08	4.03
70.5	4.00	4.19	4.39	4.35	4.30	4.26	4.21	4.17	4.13	4.08
71.0	4.05	4.23	4.44	4.39	4.35	4.30	4.26	4.22	4.17	4.13
71.5	4.09	4.27	4.48	4.44	4.40	4.35	4.31	4.26	4.22	4.18
72.0	4.13	4.31	4.53	4.49	4.44	4.40	4.35	4.31	4.27	4.22
72.5	4.17	4.36	4.58	4.53	4.49	4.45	4.40	4.36	4.31	4.27
73.0	4.21	4.40	4.62	4.58	4.54	4.49	4.45	4.40	4.36	4.32
73.5	4.26	4.44	4.67	4.63	4.50	4.54	4.50	4.45	4.41	4.36

Extracted by GlobalMSDS Ltd

12 March 2019

74.0	4.30	4.48	4.72	4.67	4.63	4.59	4.54	4.50	4.45	4.41
74.5	4.34	4.52	4.77	4.72	4.68	4.63	4.59	4.55	4.50	4.46
75.0	4.38	4.57	4.81	4.77	4.72	4.68	4.64	4.59	4.55	4.50
75.5	4.42	4.61	4.86	4.82	4.77	4.73	4.68	4.64	4.60	4.55
76.0	4.47	4.65	4.91	4.86	4.82	4.77	4.73	4.69	4.64	4.60
76.5	4.51	4.69	4.95	4.91	4.87	4.82	4.78	4.73	4.69	4.65
77.0	4.55	4.73	5.00	4.96	4.91	4.87	4.82	4.78	4.74	4.69

APPENDIX C -- Spirometry Prediction Tables for Normal Males and Females (Continued)

TABLE 3. PREDICTED FVC FOR FEMALES (KNUDSON, ET AL.:

AM. REV. RESPIR. DIS. 1976, 113, 587.)

AGE

HT	37	39	41	43	45	47	49	51
52.0	2.30	2.25	2.21	2.17	2.12	2.08	2.03	1.99
52.5	2.35	2.30	2.26	2.21	2.17	2.13	2.08	2.04
53.0	2.39	2.35	2.30	2.26	2.22	2.17	2.13	2.08
53.5	2.44	2.40	2.35	2.31	2.26	2.22	2.18	2.13
54.0	2.49	2.44	2.40	2.35	2.31	2.27	2.22	2.18
54.5	2.53	2.49	2.45	2.40	2.36	2.31	2.27	2.23
55.0	2.58	2.54	2.49	2.45	2.40	2.36	2.32	2.27
55.5	2.63	2.58	2.54	2.50	2.45	2.41	2.36	2.32
56.0	2.67	2.63	2.59	2.54	2.50	2.45	2.41	2.37
56.5	2.72	2.68	2.63	2.59	2.55	2.50	2.46	2.41
57.0	2.77	2.72	2.68	2.64	2.59	2.55	2.50	2.46
57.5	2.82	2.77	2.73	2.68	2.64	2.60	2.55	2.51
58.0	2.86	2.82	2.77	2.73	2.69	2.64	2.60	2.55
58.5	2.91	2.87	2.82	2.78	2.73	2.69	2.65	2.60
59.0	2.96	2.91	2.87	2.82	2.78	2.74	2.69	2.65
59.5	3.00	2.96	2.92	2.87	2.83	2.78	2.74	2.70

Extracted by GlobalMSDS Ltd

1	2	M	arc	h	20	119
1	_	111	arc.	11	∠∪	ノエノ

60.0	3.05	3.01	2.96	2.92	2.87	2.83	2.79	2.74
60.5	3.10	3.05	3.01	2.97	2.92	2.88	2.83	2.79
61.0	3.14	3.10	3.06	3.01	2.97	2.92	2.88	2.84
61.5	3.19	3.15	3.10	3.06	3.02	2.97	2.93	2.88
62.0	3.24	3.19	3.15	3.11	3.06	3.02	2.97	2.93
62.5	3.29	3.24	3.20	3.15	3.11	3.07	3.02	2.98
63.0	3.33	3.29	3.24	3.20	3.16	3.11	3.07	3.02
63.5	3.38	3.34	3.29	3.25	3.20	3.16	3.12	3.07
64.0	3.43	3.38	3.34	3.29	3.25	3.21	3.16	3.12
64.5	3.47	3.43	3.39	3.34	3.30	3.25	3.21	3.17
65.0	3.52	3.48	3.43	3.39	3.34	3.30	3.26	3.21
65.5	3.57	3.52	3.48	3.44	3.39	3.35	3.30	3.26
66.0	3.61	3.57	3.53	3.48	3.44	3.39	3.35	3.31
66.5	3.66	3.62	3.57	3.53	3.49	3.44	3.40	3.35
67.0	3.71	3.66	3.62	3.58	3.53	3.49	3.44	3.40
67.5	3.76	3.71	3.67	3.62	3.58	3.54	3.49	3.45
68.0	3.80	3.76	3.71	3.67	3.63	3.58	3.54	3.49
68.5	3.85	3.81	3.76	3.72	3.67	3.63	3.59	3.54
69.0	3.90	3.85	3.81	3.76	3.72	3.68	3.63	3.59
69.5	3.94	3.90	3.86	3.81	3.77	3.72	3.68	3.64
70.0	3.99	3.95	3.90	3.86	3.81	3.77	3.73	3.68
70.5	4.04	3.99	3.95	3.91	3.86	3.82	3.77	3.73
71.0	4.08	4.04	4.00	3.95	3.91	3.86	3.82	3.78
71.5	4.13	4.09	4.04	4.00	3.96	3.91	3.87	3.82
72.0	4.18	4.13	4.09	4.05	4.00	3.96	3.91	3.87
72.5	4.23	4.18	4.14	4.09	4.05	4.01	3.96	3.92
73.0	4.27	4.23	4.18	4.14	4.10	4.05	4.01	3.96
73.5	4.32	4.28	4.23	4.19	4.14	4.10	4.06	4.01
74.0	4.37	4.32	4.28	4.23	4.19	4.15	4.10	4.06
74.5	4.41	4.37	4.33	4.28	4.24	4.19	4.15	4.11
75.0	4.46	4.42	4.37	4.33	4.28	4.24	4.20	4.15
75.5	4.51	4.46	4.42	4.38	4.33	4.29	4.24	4.20
76.0	4.55	4.51	4.47	4.42	4.38	4.33	4.29	4.25
76.5	4.60	4.56	4.51	4.47	4.43	4.38	4.34	4.29

Extracted by GlobalMSDS Ltd 12 March 2019

77.0 4.65 4.60 4.56 4.52 4.47 4.43 4.38 4.34

APPENDIX C -- Spirometry Prediction Tables for

Normal Males and Females (Continued)

TABLE 3. PREDICTED FVC FOR FEMALES (KNUDSON, ET AL.:

AM. REV. RESPIR. DIS. 1976, 113, 587.)

AGE 53 55 57 59 61 63 65 52.0 1.95 1.90 1.86 1.81 1.77 1.73 1.68 52.5 1.99 1.95 1.91 1.86 1.82 1.77 1.73 53.0 2.04 2.00 1.95 1.91 1.86 1.82 1.78 53.5 2.09 2.04 2.00 1.96 1.91 1.87 1.82 54.0 2.13 2.09 2.05 2.00 1.96 1.91 1.87 54.5 2.18 2.14 2.09 2.05 2.01 1.96 1.92 55.0 2.23 2.18 2.14 2.10 2.05 2.01 1.96 55.5 2.28 2.23 2.19 2.14 2.10 2.06 2.01 56.0 2.32 2.28 2.23 2.19 2.15 2.10 2.06 56.5 2.37 2.33 2.28 2.24 2.19 2.15 2.11 57.0 2.42 2.37 2.33 2.28 2.24 2.20 2.15 57.5 2.46 2.42 2.38 2.33 2.29 2.24 2.20 58.0 2.51 2.47 2.42 2.38 2.33 2.29 2.25 58.5 2.56 2.51 2.47 2.43 2.38 2.34 2.29 59.0 2.60 2.56 2.52 2.47 2.43 2.38 2.34 59.5 2.65 2.61 2.56 2.52 2.48 2.43 2.39 60.0 2.70 2.65 2.61 2.57 2.52 2.48 2.43 60.5 2.75 2.70 2.66 2.61 2.57 2.53 2.48 61.0 2.79 2.75 2.70 2.66 2.62 2.57 2.53 61.5 2.84 2.80 2.75 2.71 2.66 2.62 2.58 62.0 2.89 2.84 2.80 2.75 2.71 2.67 2.62 62.5 2.93 2.89 2.85 2.80 2.76 2.71 2.67

Extracted by GlobalMSDS Ltd

12 March 2019

63.0	2.98	2.94	2.89	2.85	2.80	2.76	2.72
63.5	3.03	2.98	2.94	2.90	2.85	2.81	2.76
64.0	3.07	3.03	2.99	2.94	2.90	2.85	2.81
64.5	3.12	3.08	3.03	2.99	2.95	2.90	2.86
65.0	3.17	3.12	3.08	3.04	2.99	2.95	2.90
65.5	3.22	3.17	3.13	3.08	3.04	3.00	2.95
66.0	3.26	3.22	3.17	3.13	3.09	3.04	3.00
66.5	3.31	3.27	3.22	3.18	3.13	3.09	3.05
67.0	3.36	3.31	3.27	3.22	3.18	3.14	3.09
67.5	3.40	3.36	3.32	3.27	3.23	3.18	3.14
68.0	3.45	3.41	3.36	3.32	3.27	3.23	3.19
68.5	3.50	3.45	3.41	3.37	3.32	3.28	3.23
69.0	3.54	3.50	3.46	3.41	3.37	3.32	3.28
69.5	3.59	3.55	3.50	3.46	3.42	3.37	3.33
70.0	3.64	3.59	3.55	3.51	3.46	3.42	3.37
70.5	3.69	3.64	3.60	3.55	3.51	3.47	3.42
71.0	3.73	3.69	3.64	3.60	3.56	3.51	3.47
71.5	3.78	3.74	3.69	3.65	3.60	3.56	3.52
72.0	3.83	3.78	3.74	3.69	3.65	3.61	3.56
72.5	3.87	3.83	3.79	3.74	3.70	3.65	3.61
73.0	3.92	3.88	3.83	3.79	3.74	3.70	3.66
73.5	3.97	3.92	3.88	3.84	3.79	3.75	3.70
74.0	4.01	3.97	3.93	3.88	3.84	3.79	3.75
74.5	4.06	4.02	3.97	3.93	3.89	3.84	3.80
75.0	4.11	4.06	4.02	3.98	3.93	3.89	3.84
75.5	4.16	4.11	4.07	4.02	3.98	3.94	3.89
76.0	4.20	4.16	4.11	4.07	4.03	3.98	3.94
76.5	4.25	4.21	4.16	4.12	4.07	4.03	3.99
77.0	4.30	4.25	4.21	4.16	4.12	4.08	4.03

Extracted by GlobalMSDS Ltd 12 March 2019

Normal Males and Females

TABLE 4. PREDICTED FEV(1) FOR FEMALES

(KNUDSON, ET AL.: AM. REV. RESPIR. DIS. 1976, 113, 587.)

	AGE									
НТ	17	19	21	23	25	27	29	31	33	35
52.0	2.31	2.48	2.33	2.29	2.25	2.21	2.16	2.12	2.08	2.04
52.5	2.34	2.51	2.37	2.32	2.28	2.24	2.20	2.16	2.11	2.07
53.0	2.38	2.55	2.40	2.36	2.32	2.27	2.23	2.19	2.15	2.11
53.5	2.41	2.58	2.43	2.39	2.35	2.31	2.27	2.22	2.18	2.14
54.0	2.45	2.62	2.47	2.43	2.38	2.34	2.30	2.26	2.22	2.17
54.5	2.48	2.65	2.50	2.46	2.42	2.38	2.33	2.29	2.25	2.21
55.0	2.51	2.68	2.54	2.49	2.45	2.41	2.37	2.33	2.28	2.24
55.5	2.55	2.72	2.57	2.53	2.49	2.45	2.40	2.36	2.32	2.28
56.0	2.58	2.75	2.61	2.56	2.52	2.48	2.44	2.40	2.35	2.31
56.5	2.62	2.79	2.64	2.60	2.56	2.51	2.47	2.43	2.39	2.35
57.0	2.65	2.82	2.67	2.63	2.59	2.55	2.51	2.46	2.42	2.38
57.5	2.69	2.86	2.71	2.67	2.62	2.58	2.54	2.50	2.46	2.41
58.0	2.72	2.89	2.74	2.70	2.66	2.62	2.57	2.53	2.49	2.45
58.5	2.75	2.92	2.78	2.73	2.69	2.65	2.61	2.57	2.52	2.48
59.0	2.79	2.96	2.81	2.77	2.73	2.69	2.64	2.60	2.56	2.52
59.5	2.82	2.99	2.85	2.80	2.76	2.72	2.68	2.64	2.59	2.55
60.0	2.86	3.03	2.88	2.84	2.80	2.75	2.71	2.67	2.63	2.59
60.5	2.89	3.06	2.91	2.87	2.83	2.79	2.75	2.70	2.66	2.62
61.0	2.93	3.10	2.95	2.91	2.86	2.82	2.78	2.74	2.70	2.65
61.5	2.96	3.13	2.98	2.94	2.90	2.86	2.81	2.77	2.73	2.69
62.0	2.99	3.16	3.02	2.97	2.93	2.89	2.85	2.81	2.76	2.72
62.5	3.03	3.20	3.05	3.01	2.97	2.93	2.88	2.84	2.80	2.76
63.0	3.06	3.23	3.09	3.04	3.00	2.96	2.92	2.88	2.83	2.79
63.5	3.10	3.27	3.12	3.08	3.04	2.99	2.95	2.91	2.87	2.83
64.0	3.13	3.30	3.15	3.11	3.07	3.03	2.99	2.94	2.90	2.86
64.5	3.17	3.34	3.19	3.15	3.10	3.06	3.02	2.98	2.94	2.89

65.0 3.20 3.37 3.22 3.18 3.14 3.10 3.05 3.01 2.97 2.93

Extracted by GlobalMSDS Ltd

12 March 2019

65.5	3.23	3.40	3.26	3.21	3.17	3.13	3.09	3.05	3.00	2.96
66.0	3.27	3.44	3.29	3.25	3.21	3.17	3.12	3.08	3.04	3.00
66.5	3.30	3.47	3.33	3.28	3.24	3.20	3.16	3.12	3.07	3.03
67.0	3.34	3.51	3.36	3.32	3.28	3.23	3.19	3.15	3.11	3.07
67.5	3.37	3.54	3.39	3.35	3.31	3.27	3.23	3.18	3.14	3.10
68.0	3.41	3.58	3.43	3.39	3.34	3.30	3.26	3.22	3.18	3.13
68.5	3.44	3.61	3.46	3.42	3.38	3.34	3.29	3.25	3.21	3.17
69.0	3.47	3.64	3.50	3.46	3.41	3.37	3.33	3.29	3.25	3.20
69.5	3.51	3.68	3.53	3.49	3.45	3.41	3.36	3.32	3.28	3.24
70.0	3.54	3.71	3.57	3.52	3.48	3.44	3.40	3.36	3.31	3.27
70.5	3.58	3.75	3.60	3.56	3.52	3.47	3.43	3.39	3.35	3.31
71.0	3.61	3.78	3.63	3.59	3.55	3.51	3.47	3.42	3.38	3.34
71.5	3.65	3.82	3.67	3.63	3.58	3.54	3.50	3.46	3.42	3.37
72.0	3.68	3.85	3.70	3.66	3.62	3.58	3.53	3.49	3.45	3.41
72.5	3.71	3.88	3.74	3.70	3.65	3.61	3.57	3.53	3.49	3.44
73.0	3.75	3.92	3.77	3.73	3.69	3.65	3.60	3.56	3.52	3.48
73.5	3.78	3.95	3.81	3.76	3.72	3.68	3.64	3.60	3.55	3.51
74.0	3.82	3.99	3.84	3.80	3.76	3.71	3.67	3.63	3.59	3.55
74.5	3.85	4.02	3.87	3.83	3.79	3.75	3.71	3.66	3.62	3.58
75.0	3.89	4.06	3.91	3.87	3.82	3.78	3.74	3.70	3.66	3.61
75.5	3.92	4.09	3.94	3.90	3.86	3.82	3.77	3.73	3.69	3.65
76.0	3.95	4.12	3.98	3.94	3.89	3.85	3.81	3.77	3.73	3.68
76.5	3.99	4.16	4.01	3.97	3.93	3.89	3.84	3.80	3.76	3.72
77.0	4.02	4.19	4.05	4.00	3.96	3.92	3.88	3.84	3.79	3.75

APPENDIX C -- Spirometry Prediction Tables for Normal Males and Females (Continued)

TABLE 4. PREDICTED FEV(1) FOR FEMALES

(KNUDSON, ET AL.: AM. REV. RESPIR. DIS. 1976, 113, 587.)

Extracted by GlobalMSDS Ltd 12 March 2019

	AGE							
HT	37	39	41	43	45	47	49	51
52.0	2.00	1.95	1.91	1.87	1.83	1.79	1.74	1.70
52.5	2.03	1.99	1.95	1.90	1.86	1.82	1.78	1.74
53.0	2.06	2.02	1.98	1.94	1.90	1.85	1.81	1.77
53.5	2.10	2.06	2.01	1.97	1.93	1.89	1.85	1.80
54.0	2.13	2.09	2.05	2.01	1.96	1.92	1.88	1.84
54.5	2.17	2.12	2.08	2.04	2.00	1.96	1.91	1.87
55.0	2.20	2.16	2.12	2.07	2.03	1.99	1.95	1.91
55.5	2.24	2.19	2.15	2.11	2.07	2.03	1.98	1.94
56.0	2.27	2.23	2.19	2.14	2.10	2.06	2.02	1.98
56.5	2.30	2.26	2.22	2.18	2.14	2.09	2.05	2.01
57.0	2.34	2.30	2.25	2.21	2.17	2.13	2.09	2.04
57.5	2.37	2.33	2.29	2.25	2.20	2.16	2.12	2.08
58.0	2.41	2.36	2.32	2.28	2.24	2.20	2.15	2.11
58.5	2.44	2.40	2.36	2.31	2.27	2.23	2.19	2.15
59.0	2.48	2.43	2.39	2.35	2.31	2.27	2.22	2.18
59.5	2.51	2.47	2.43	2.38	2.34	2.30	2.26	2.22
60.0	2.54	2.50	2.46	2.42	2.38	2.33	2.29	2.25
60.5	2.58	2.54	2.49	2.45	2.41	2.37	2.33	2.28
61.0	2.61	2.57	2.53	2.49	2.44	2.40	2.36	2.32
61.5	2.65	2.60	2.56	2.52	2.48	2.44	2.39	2.35
62.0	2.68	2.64	2.60	2.55	2.51	2.47	2.43	2.39
62.5	2.72	2.67	2.63	2.59	2.55	2.51	2.46	2.42
63.0	2.75	2.71	2.67	2.62	2.58	2.54	2.50	2.46
63.5	2.78	2.74	2.70	2.66	2.62	2.57	2.53	2.49
64.0	2.82	2.78	2.73	2.69	2.65	2.61	2.57	2.52
64.5	2.85	2.81	2.77	2.73	2.68	2.64	2.60	2.56
65.0	2.89	2.84	2.80	2.76	2.72	2.68	2.63	2.59
65.5	2.92	2.88	2.84	2.79	2.75	2.71	2.67	2.63
66.0	2.96	2.91	2.87	2.83	2.79	2.75	2.70	2.66
66.5	2.99	2.95	2.91	2.86	2.82	2.78	2.74	2.70
67.0	3.02	2.98	2.94	2.90	2.86	2.81	2.77	2.73

Extracted by GlobalMSDS Ltd

12 March 2019

1 2 1 1 1	iaicii 2	017						
67.5	3.06	3.02	2.97	2.94	2.89	2.85	2.81	2.76
68.0	3.09	3.05	3.01	2.97	2.92	2.88	2.84	2.80
68.5	3.13	3.08	3.04	3.00	2.96	2.92	2.87	2.83
69.0	3.16	3.12	3.08	3.04	2.99	2.95	2.91	2.87
69.5	3.20	3.15	3.11	3.07	3.03	2.99	2.94	2.90
70.0	3.23	3.19	3.15	3.10	3.06	3.02	2.98	2.94
70.5	3.26	3.22	3.18	3.14	3.10	3.05	3.01	2.97
71.0	3.30	3.26	3.21	3.17	3.13	3.09	3.05	3.00
71.5	3.33	3.29	3.25	3.21	3.16	3.12	3.08	3.04
72.0	3.37	3.32	3.28	3.24	3.20	3.16	3.11	3.07
72.5	3.40	3.36	3.32	3.28	3.23	3.19	3.15	3.11
73.0	3.44	3.39	3.35	3.31	3.27	3.23	3.18	3.14
73.5	3.47	3.43	3.39	3.34	3.30	3.26	3.22	3.18
74.0	3.50	3.46	3.42	3.38	3.34	3.29	3.25	3.21
74.5	3.54	3.50	3.45	3.41	3.37	3.33	3.29	3.24
75.0	3.57	3.53	3.49	3.45	3.40	3.36	3.32	3.28
75.5	3.61	3.56	3.52	3.48	3.44	3.40	3.35	3.31
76.0	3.64	3.60	3.56	3.52	3.47	3.43	3.39	3.35
76.5	3.68	3.63	3.59	3.55	3.51	3.47	3.42	3.38
77.0	3.71	3.67	3.63	3.58	3.54	3.50	3.46	3.42

```
APPENDIX C -- Spirometry Prediction Tables for Normal Males and Females (Continued)
```

```
TABLE 4. PREDICTED FEV(1) FOR FEMALES

(KNUDSON, ET AL.: AM. REV. RESPIR. DIS. 1976, 113, 587.)
```

```
AGE

HT 53 55 57 59 61 63 65

52.0 1.66 1.62 1.58 1.53 1.49 1.45 1.41
```

Extracted by GlobalMSDS Ltd

12 March 2019)
---------------	---

52.5	1.69	1.65	1.61	1.57	1.53	1.48	1.44
53.0	1.73	1.69	1.64			1.52	1.44
53.5		1.72	1.68	1.60	1.56		
	1.76					1.55	1.51
54.0	1.80	1.75	1.71	1.67	1.63	1.59	1.54
54.5	1.83	1.79	1.75	1.70	1.66	1.62	1.58
55.0	1.86	1.82	1.78	1.74	1.70	1.65	1.61
55.5	1.90	1.86	1.82	1.77	1.73	1.69	1.65
56.0	1.93	1.89	1.85	1.81	1.77	1.72	1.68
56.5	1.97	1.93	1.88	1.84	1.80	1.76	1.72
57.0	2.00	1.96	1.92	1.88	1.83	1.79	1.75
57.5	2.04	1.99	1.95	1.91	1.87	1.83	1.78
58.0	2.07	2.03	1.99	1.94	1.90	1.86	1.82
58.5	2.10	2.06	2.02	1.98	1.94	1.89	1.85
59.0	2.14	2.10	2.06	2.01	1.97	1.93	1.89
59.5	2.17	2.13	2.09	2.05	2.01	1.96	1.92
60.0	2.21	2.17	2.12	2.08	2.04	2.00	1.96
60.5	2.24	2.20	2.16	2.12	2.07	2.03	1.99
61.0	2.28	2.23	2.19	2.15	2.11	2.07	2.02
61.5	2.31	2.27	2.23	2.18	2.14	2.10	2.06
62.0	2.34	2.30	2.26	2.22	2.18	2.13	2.09
62.5	2.38	2.34	2.30	2.25	2.21	2.17	2.13
63.0	2.41	2.37	2.33	2.29	2.25	2.20	2.16
63.5	2.45	2.41	2.36	2.32	2.28	2.24	2.20
64.0	2.48	2.44	2.40	2.36	2.31	2.27	2.23
64.5	2.52	2.47	2.43	2.39	2.35	2.31	2.26
65.0	2.55	2.51	2.47	2.42	2.38	2.34	2.30
65.5	2.58	2.54	2.50	2.46	2.42	2.37	2.33
66.0	2.62	2.58	2.54	2.49	2.45	2.41	2.37
66.5	2.65	2.61	2.57	2.53	2.49	2.44	2.40
67.0	2.69	2.65	2.60	2.56	2.52	2.48	2.44
67.5	2.72	2.68	2.64	2.60	2.55	2.51	2.47
68.0	2.76	2.71	2.67	2.63	2.59	2.55	2.50
68.5	2.79	2.75	2.71	2.66	2.62	2.58	2.54
69.0	2.83	2.78	2.74	2.70		2.62	2.57

Extracted by GlobalMSDS Ltd

12 March 2019

69.5	2.86	2.82	2.78	2.73	2.69	2.65	2.61
70.0	2.89	2.85	2.81	2.77	2.73	2.68	2.64
70.5	2.93	2.89	2.84	2.80	2.76	2.72	2.68
71.0	2.96	2.92	2.88	2.84	2.79	2.75	2.71
71.5	3.00	2.95	2.91	2.87	2.83	2.79	2.74
72.0	3.03	2.99	2.95	2.90	2.86	2.82	2.78
72.5	3.07	3.02	2.98	2.94	2.90	2.86	2.81
73.0	3.10	3.06	3.02	2.97	2.93	2.89	2.85
73.5	3.13	3.09	3.05	3.01	2.97	2.92	2.88
74.0	3.17	3.13	3.08	3.04	3.00	2.96	2.92
74.5	3.20	3.16	3.12	3.08	3.03	2.99	2.95
75.0	3.24	3.19	3.15	3.11	3.07	3.03	2.98
75.5	3.27	3.23	3.19	3.14	3.10	3.06	3.02
76.0	3.31	3.26	3.22	3.18	3.14	3.10	3.05
76.5	3.34	3.30	3.26	3.21	3.17	3.13	3.09
77.0	3.37	3.33	3.29	3.25	3.21	3.16	3.12

The spirometric measurements of pulmonary function shall conform to the following minimum standards, and these standards are not intended to preclude additional testing or alternate methods which can be determined to be superior.

I. APPARATUS

- a. The instrument shall be accurate to within + or 50 milliliters or within + or 3 percent of reading, whichever is greater.
- b. The instrument should be capable of measuring vital capacity from 0 to 7 liters BTPS.
- c. The instrument shall have a low inertia and offer low resistance to airflow such that the resistance to airflow at 12 liters per second must be less than 1.5 cm H2O/(liter/sec).
- d. The zero time point for the purpose of timing the FEV(1) shall be determined by extrapolating the steepest portion of the volume time curve back to the maximal inspiration volume (1, 2, 3, 4) or by an equivalent method.
- e. Instruments incorporating measurements of airflow to determine volume shall conform to the same volume accuracy stated in (a) of this section when presented with flow rates from at least 0 to 12 liters per second.
- f. The instrument or user of the instrument must have a means of correcting volumes to body temperature saturated with water vapor (BTPS) under conditions of varying ambient spirometer temperatures and barometric pressures.
- g. The instrument used shall provide a tracing or display of either flow versus volume or volume versus time during the entire forced expiration. A tracing or display is necessary to determine whether the patient has performed the test properly. The tracing must be stored and available for recall and must be of sufficient size that hand measurements may be made within requirement of paragraph (a) of this section. If a paper record is made it must have a paper speed of at least 2 cm/sec and a volume sensitivity of at least 10.0 mm of chart per liter of volume.

Extracted by GlobalMSDS Ltd

12 March 2019

- h. The instrument shall be capable of accumulating volume for a minimum of 10 seconds and shall not stop accumulating volume before (1) the volume change for a 0.5 second interval is less than 25 milliliters, or (2) the flow is less than 50 milliliters per second for a 0.5 second interval.
- i. The forced vital capacity (FVC) and forced expiratory volume in 1 second (FEV(1).(0) measurements shall comply with the accuracy requirements stated in paragraph (a) of this section. That is, they should be accurately measured to within + or 50 ml or within + or 3 percent of reading, whichever is greater.
- j. The instrument must be capable of being calibrated in the field with respect to the FEV(1) and FVC. This calibration of the FEV(1) and FVC may be either directly or indirectly through volume and time base measurements. The volume calibration source should provide a volume displacement of at least 2 liters and should be accurate to within + or 30 milliliters.

II. TECHNIQUE FOR MEASUREMENT OF FORCED VITAL CAPACITY MANEUVER

a. Use of a nose clip is recommended but not required. The procedures shall be explained in simple terms to the patient who shall be instructed to loosen any tight clothing and stand in front of the apparatus. The subject may sit, but care should be taken on repeat testing that the same position be used and, if possible, the same spirometer. Particular attention shall be given to insure that the chin is slightly elevated with the neck slightly extended. The patient shall be instructed to make a full inspiration from a normal breathing pattern and then blow into the apparatus, without interruption, as hard, fast, and completely as possible. At least three forced expirations shall be carried out. During the maneuvers, the patient shall be observed for compliance with instruction. The expirations shall be checked visually for reproducibility from flow-volume or volume-time tracings or displays.

The following efforts shall be judged unacceptable when the patient:

- 1. Has not reached full inspiration preceding the forced expiration,
- 2. Has not used maximal effort during the entire forced expiration,
- 3. Has not continued the expiration for at least 5 seconds or until an obvious plateau in the volume time curve has occurred,
- 4. Has coughed or closed his glottis,
- 5. Has an obstructed mouthpiece or a leak around the mouthpiece (obstruction due to tongue being placed in front of mouthpiece, false teeth falling in front of mouthpiece, etc.)
- 6. Has an unsatisfactory start of expiration, one characterized by excessive hesitation (or false starts), and therefore not allowing back extrapolation of time 0 (extrapolated volume on the volume time tracing must be less than 10 percent of the FVC.)
- 7. Has an excessive variability between the three acceptable curves. The variation between the two largest FVC's and FEV(1)'s of the three satisfactory tracings should not exceed 10 percent or + or 100 milliliters, whichever is greater.
- b. Periodic and routine recalibration of the instrument or method for recording FVC and FEV(1).(0) should be performed using a syringe or other volume source of at least 2 liters.

III. INTERPRETATION OF SPIROGRAM

- a. The first step in evaluating a spirogram should be to determine whether or not the patient has performed the test properly or as described in II above. From the three satisfactory tracings, the forced vital capacity (FVC) and forced expiratory volume in 1 second (FEV(1).(0)) shall be measured and recorded. The largest observed FVC and largest observed FEV(1) shall be used in the analysis regardless of the curve(s) on which they occur.
- b. The following guidelines are recommended by NIOSH for the evaluation and management of workers exposed to cotton dust. It is important to note that employees who show reductions in FEV(1)/FVC ratio below .75 or drops in Monday FEV(1) of 5 percent or greater on their initial screening exam, should be re-evaluated within a month of the first exam. Those who show consistent decrease in lung function, as shown on the following table, should be managed as recommended.

IV. QUALIFICATIONS OF PERSONNEL ADMINISTERING THE TEST

Extracted by GlobalMSDS Ltd

12 March 2019

Technicians who perform pulmonary function testing should have the basic knowledge required to produce meaningful results. Training consisting of approximately 16 hours of formal instruction should cover the following areas.

- a. Basic physiology of the forced vital capacity maneuver and the determinants of airflow limitation with emphasis on the relation to reproducibility of results.
- b. Instrumentation requirements including calibration procedures, sources of error and their correction.
- c. Performance of the testing including subject coaching, recognition of improperly performed maneuvers and corrective actions.
- d. Data quality with emphasis on reproducibility.
- e. Actual use of the equipment under supervised conditions.
- f. Measurement of tracings and calculations of results.

The spirometric measurements of pulmonary function shall conform to the following minimum standards, and these standards are not intended to preclude additional testing or alternate methods which can be determined to be superior.

I. APPARATUS

- a. The instrument shall be accurate to within + or 50 milliliters or within + or 3 percent of reading, whichever is greater.
- b. The instrument should be capable of measuring vital capacity from 0 to 7 liters BTPS.
- c. The instrument shall have a low inertia and offer low resistance to airflow such that the resistance to airflow at 12 liters per second must be less than 1.5 cm H2O/(liter/sec).
- d. The zero time point for the purpose of timing the FEV(1) shall be determined by extrapolating the steepest portion of the volume time curve back to the maximal inspiration volume (1, 2, 3, 4) or by an equivalent method.
- e. Instruments incorporating measurements of airflow to determine volume shall conform to the same volume accuracy stated in (a) of this section when presented with flow rates from at least 0 to 12 liters per second.
- f. The instrument or user of the instrument must have a means of correcting volumes to body temperature saturated with water vapor (BTPS) under conditions of varying ambient spirometer temperatures and barometric pressures.
- g. The instrument used shall provide a tracing or display of either flow versus volume or volume versus time during the entire forced expiration. A tracing or display is necessary to determine whether the patient has performed the test properly. The tracing must be stored and available for recall and must be of sufficient size that hand measurements may be made within requirement of paragraph (a) of this section. If a paper record is made it must have a paper speed of at least 2 cm/sec and a volume sensitivity of at least 10.0 mm of chart per liter of volume.
- h. The instrument shall be capable of accumulating volume for a minimum of 10 seconds and shall not stop accumulating volume before (1) the volume change for a 0.5 second interval is less than 25 milliliters, or (2) the flow is less than 50 milliliters per second for a 0.5 second interval.
- i. The forced vital capacity (FVC) and forced expiratory volume in 1 second (FEV(1).(0) measurements shall comply with the accuracy requirements stated in paragraph (a) of this section. That is, they should be accurately measured to within + or 50 ml or within + or 3 percent of reading, whichever is greater.
- j. The instrument must be capable of being calibrated in the field with respect to the FEV(1) and FVC. This calibration of the FEV(1) and FVC may be either directly or indirectly through volume and time base measurements. The volume calibration source should provide a volume displacement of at least 2 liters and should be accurate to within + or 30 milliliters.

II. TECHNIQUE FOR MEASUREMENT OF FORCED VITAL CAPACITY MANEUVER

a. Use of a nose clip is recommended but not required. The procedures shall be explained in simple terms to the patient who shall be instructed to loosen any tight clothing and stand in front of

Extracted by GlobalMSDS Ltd

12 March 2019

the apparatus. The subject may sit, but care should be taken on repeat testing that the same position be used and, if possible, the same spirometer. Particular attention shall be given to insure that the chin is slightly elevated with the neck slightly extended. The patient shall be instructed to make a full inspiration from a normal breathing pattern and then blow into the apparatus, without interruption, as hard, fast, and completely as possible. At least three forced expirations shall be carried out. During the maneuvers, the patient shall be observed for compliance with instruction. The expirations shall be checked visually for reproducibility from flow-volume or volume-time tracings or displays.

The following efforts shall be judged unacceptable when the patient:

- 1. Has not reached full inspiration preceding the forced expiration,
- 2. Has not used maximal effort during the entire forced expiration,
- 3. Has not continued the expiration for at least 5 seconds or until an obvious plateau in the volume time curve has occurred,
- 4. Has coughed or closed his glottis,
- 5. Has an obstructed mouthpiece or a leak around the mouthpiece (obstruction due to tongue being placed in front of mouthpiece, false teeth falling in front of mouthpiece, etc.)
- 6. Has an unsatisfactory start of expiration, one characterized by excessive hesitation (or false starts), and therefore not allowing back extrapolation of time 0 (extrapolated volume on the volume time tracing must be less than 10 percent of the FVC.)
- 7. Has an excessive variability between the three acceptable curves. The variation between the two largest FVC's and FEV(1)'s of the three satisfactory tracings should not exceed 10 percent or + or 100 milliliters, whichever is greater.
- b. Periodic and routine recalibration of the instrument or method for recording FVC and FEV(1).(0) should be performed using a syringe or other volume source of at least 2 liters.

III. INTERPRETATION OF SPIROGRAM

- a. The first step in evaluating a spirogram should be to determine whether or not the patient has performed the test properly or as described in II above. From the three satisfactory tracings, the forced vital capacity (FVC) and forced expiratory volume in 1 second (FEV(1).(0)) shall be measured and recorded. The largest observed FVC and largest observed FEV(1) shall be used in the analysis regardless of the curve(s) on which they occur.
- b. The following guidelines are recommended by NIOSH for the evaluation and management of workers exposed to cotton dust. It is important to note that employees who show reductions in FEV(1)/FVC ratio below .75 or drops in Monday FEV(1) of 5 percent or greater on their initial screening exam, should be re-evaluated within a month of the first exam. Those who show consistent decrease in lung function, as shown on the following table, should be managed as recommended.

IV. QUALIFICATIONS OF PERSONNEL ADMINISTERING THE TEST

Technicians who perform pulmonary function testing should have the basic knowledge required to produce meaningful results. Training consisting of approximately 16 hours of formal instruction should cover the following areas.

- a. Basic physiology of the forced vital capacity maneuver and the determinants of airflow limitation with emphasis on the relation to reproducibility of results.
- b. Instrumentation requirements including calibration procedures, sources of error and their correction.
- c. Performance of the testing including subject coaching, recognition of improperly performed maneuvers and corrective actions.
- d. Data quality with emphasis on reproducibility.
- e. Actual use of the equipment under supervised conditions.
- f. Measurement of tracings and calculations of results.